

Nevada Fire Service Certification System

Fire Fighter I Candidate Manipulative Skills Manual

Fire & Hazardous Material Training & Certification Bureau Revised July 2024





Nevada Fire Service Certification System Fire Fighter I Skills Manual

FIREFIGHTER I MANIPULATIVE SKILL OBJECTIVES

GENERAL

PERSONAL PROTECTIVE EQUIPMENT

- 1- Demonstrate the care, inspection, and maintenance of protective clothing assigned or available for use.
 - REFERENCE:NFPA 1001, 2019 Edition, 4.1.2CONDITION:Given helmet with eye protection (per NFPA 1500 Helmet face
visor is not considered appropriate eye protection), Hood, Boots,
Gloves, Coat, and Pants.COMPETENCE:• Standard or code materials
• Inspect all equipment for damage.
 - Remove dirt, chemicals, oil or other compounds from protective clothing.
 - Inspect helmet and visor for damage.
 - Inspect suspenders for damage or loss of support.
 - Describe proper cleaning methods (Manufacturer
 - recommended or department SOP).

2- Demonstrate donning and doffing structural firefighter protective clothing.

- REFERENCE:NFPA 1001, 2019 Edition, 4.1.2CONDITION:Given helmet with eye protection (per NFPA 1500 Helmet face
visor is not considered appropriate eye protection), Hood, Boots,
Gloves, Coat and Pants.COMPETENCE:• Don Hood (hood maybe rolled down around collar of coat).
• Don and fasten all closures on pants/boots and coat.
• Collar turned up on coat.DevelopmentDevelopmentDevelopmentDevelopment
 - Don helmet and tighten chin strap (helmet ear flaps down).
 - Don gloves.
 - Doff protective clothing and place back in-service.

<u>ROPES</u>

3- Demonstrate the hoisting of the following tools: fire axe, pike pole, roof ladder, and hose line (charged/dry).

REFERENCE:	NFPA 1001, 2019 Edition, 4.1.2, 4.3.11b, 4.3.12b & 4.3.20
CONDITION:	Wearing full protective clothing, tool or equipment, minimum 25 ft. of rope.
COMPETENCE:	 Select tool to be hoisted. Tie with an approved knot (Skill #4A-D) for hoisting. Use "tag" line when directed. Hoist tool or equipment.

4- Demonstrate tying the following knots:

A. Bowline around waist and/or around an object (with overhand safety).

REFERENCE:	NFPA 1001, 2019 Edition, 4.1.2
CONDITION:	Given a length of rope, object such as a pole or waist.
COMPETENCE:	Select correct length of rope.Tie correct knot with overhand safety in correct position.

B. Clove hitch, running or loop method (with overhand safety).

REFERENCE:	NFPA 1001, 2019 Edition, 4.1.2
CONDITION:	Given a length of rope, object to place knot on.
COMPETENCE:	 Select correct length of rope. Tie correct knot with overhand safety in correct position.

C. Figure eight on a bight (with overhand safety).

REFERENCE:	NFPA 1001, 2019 Edition, 4.1.2
CONDITION:	Given a length of rope.
COMPETENCE:	Select correct length of rope.Tie correct knot with overhand safety in correct position.

D. Figure eight follow through (with overhand safety).

REFERENCE:	NFPA 1001, 2019 Edition, 4.1.2
CONDITION:	Given a length of rope object such as a pole or waist.
COMPETENCE:	Select correct length of rope.Tie correct knot with overhand safety in correct position.

<u>ROPES</u>

- 4- Cont: Demonstrate tying the following knots:
- E. Becket or sheet bend (with overhand safety).

REFERENCE:	NFPA 1001, 2019 Edition, 4.1.2
CONDITION:	Given 2 pieces of rope of different diameter.
COMPETENCE:	 Select correct length of rope in correct position. Larger rope should form the bight. Tie correct knot.

F. Water Knot (with overhand safety).

REFERENCE:	NFPA 1001, 2019 Edition, 4.1.2
CONDITION:	Given 12 ft. X 1 inch tubular webbing.
COMPETENCE:	Select correct length of webbing.Tie correct knot with overhand safety in correct position.

5- Demonstrate inspecting, cleaning and storing rope after use.

REFERENCE:	NFPA 1001, 2019 Edition, 4.1.2
CONDITION:	Given rope, rope bag (if available) and cleaning supplies.
COMPETENCE:	 Identify type of rope, life safety or utility. Inspect rope for damage or wear. Wash rope using approved method (verbalize). Dry rope using approved method (verbalize). Bag or coil rope. Document use of rope and inspection on rope log.

FIRE DEPARTMENT COMMUNICATIONS

RADIO AND PHONES

6- Demonstrate receiving a report of a fire or emergency situation from the public (telephone) and initiate appropriate action.

REFERENCE:	NFPA 1001, 2019 Edition, 4.2.1
CONDITION:	Given a fire or emergency scenario.
COMPETENCE:	 Identify self. Record time of call. Record type and address of incident. Record callers name and call back number. Ask questions for additional information. Hang up after caller.

7- Demonstrate receiving a business or personal telephone call from the public.

REFERENCE:	NFPA 1001, 2019 Edition, 4.2.2
CONDITION:	Given a scenario, following department SOP.
COMPETENCE:	 Identify self. Record time of call. Record message. Record callers name and call back number. Ask questions for additional information.

- Hang up after caller.
- 8- Demonstrate the use of mobile and portable radio equipment for routine or emergency traffic.

REFERENCE:	NFPA 1001, 2019 Edition, 4.2.3
CONDITION:	Given mobile/portable radio equipment.
COMPETENCE:	 Turn on power Set to correct channel Adjust volume Adjust squelch (if radio is equipped) Perform radio check (simulate) If emergency traffic, give EMERGENCY TRAFFIC signal over the air (simulated)

RADIO AND PHONES

9- Demonstrate activating an emergency call for assistance.

REFERENCE:	NFPA 1001, 2019 Edition, 4.2.4
CONDITION:	Given mobile/portable radio equipment and flashlight, wearing full protective clothing and SCBA in vision obscured conditions
COMPETENCE:	 Identify need to declare "May Day" Announce "May Day, May Day, May Day" over communications channel Provide Command with information (LUNAR) Activate PASS device Move to safe location Activate flashlight, pointed at ceiling Conserve air supply

FIREGROUND OPERATIONS

11-

SELF CONTAINED BREATHING APPARATUS

10- Identify and describe each component of the Self-Contained Breathing Apparatus (SCBA).

REFERENCE:	NFPA 1001, 2019 Edition, 4.3.1
CONDITION:	Given a Self-Contained Breathing Apparatus as used by department.
COMPETENCE:	 Backpack/harness. Air cylinder - cylinder, valve, and pressure gauge. Regulator assembly - high pressure hose, low pressure alarm, main line valve, emergency by-pass valve, secondary gauges. Facepiece assembly - low pressure hose, exhalation valve, and head harness. PASS device.
Demonstrate donning Self-Contained Breathing Apparatus (SCBA).	

NFPA 1001, 2019 Edition, 4.3.1 **REFERENCE**: CONDITION: Wearing full protective clothing and SCBA. COMPETENCE: • Check SCBA cylinder pressure gauge (verbalize pressure). • Open cylinder valve fully. Check regulator and cylinder gauge verbalize pressures (gauges should be within 100 psi of each other). • Don backpack and fasten/tighten all straps (over-the-head or coat method). • Don facepiece, adjust head harness, check seal and exhalation valve. • Don protective hood. • Attach low pressure hose to regulator or face piece. • Turn on or ensure PASS is active. • Don helmet. • Don gloves.

*Steps may vary with different SCBA's, however all of the above should be covered during the donning process.

SELF CONTAINED BREATHING APPARATUS

12- Demonstrate the following emergency procedures in the event of SCBA failure:

A. Conservation of air (skip breathing).

В.

C.

REFERENCE:	NFPA 1001, 2019 Edition, 4.3.1 Manufacture recommendations for SCBA used by department.
CONDITION:	Wearing full protective clothing and SCBA.
COMPETENCE:	 Inhale normally (as during regular breathing) Holds breath (as long as it would take to exhale) Inhale again Exhale slowly
Emergency procedu	ires in the event of a facepiece failure.
REFERENCE:	NFPA 1001, 2019 Edition, 4.3.1 Manufacture recommendations for SCBA used by department.
CONDITION:	Wearing full protective clothing, SCBA, simulated facepiece damage, 2-firefighter team.
COMPETENCE:	 Notify partner of problem. Activate emergency communications (Mayday). Notify Incident command of problem. Activate PASS. Disconnect low-pressure hose from facepiece or regulator Breath from low-pressure hose or 2nd stage regulator Exit structure with partner.
Emergency procedu	ires in the event of an interruption/restricted air flow.
REFERENCE:	NFPA 1001, 2019 Edition, 4.3.1
CONDITION:	Wearing full protective clothing, SCBA, simulated regulator damage, 2-firefighter team. Manufacture recommendations for SCBA used by department.
COMPETENCE:	 Notify partner of problem. Activate emergency communications (Mayday). Notify Incident command of problem. Close mainline valve (if applicable). Operate By-pass Open By-pass valve, inhale Close By-pass valve, Repeat as needed.

• Exit structure with partner.

SELF CONTAINED BREATHING APPARATUS

13-Doff and perform a check of an in-service SCBA: A) Without cylinder change; B) With cylinder change.

	Place SCBA on ground, close cylinder valve. Boliova avagage processory from regulator, listen for low
COMPETENCE:	A) Without cylinder change
CONDITION:	Given an SCBA and spare cylinder
REFERENCE:	NFPA 1001, 2019 Edition, 4.3.1

 Relieve excess pressure from regulator, listen for low-pressure alarm.

 Check cylinder pressure (90% full), (verbalize pressure reading).

• Disconnect regulator from facepiece or low-pressure hose from regulator.

- Fully extend all straps on SCBA backpack.
- Fully extend all straps on facepiece.
- Inspect entire apparatus for cleanliness and damage.
- * Steps may vary with different SCBA's

B) With cylinder change

- Place SCBA on ground or leave on firefighters back
- Locate a full cylinder.
- · Close cylinder valve.
- Bleed off pressure.
- Disconnect the high pressure hose from the cylinder.
- Release the cylinder closing device.
- Replace empty cylinder with a full cylinder.
- Secure full cylinder in harness.
- · Connect high pressure hose to the cylinder.
- Open the cylinder and check the operation of the gauge.
- * Steps may vary with different SCBA's

14-Demonstrate routine maintenance procedures for an in-service SCBA: Inspect, clean, and sanitize an SCBA system.

REFERENCE:	NFPA 1001, 2019 Edition, 4.5.1
	Manufacture recommendations for SCBA used by department.
CONDITION:	Given an SCBA and cleaning solution specified by manufacturer
COMPETENCE:	 Inspect SCBA and facepiece. Wash facepiece and sanitize (verbalize sanitation procedure). Rinse in fresh water, hang to dry. Wash/rinse backpack (keep water from optoring regulator).

Wash/rinse backpack (keep water from entering regulator).

EMERGENCY RESPONSE - APPARATUS

15- Demonstrate safety procedures for mounting, use of seat belts, hearing protection and other safety equipment on apparatus, safely dismounting fire apparatus.

REFERENCE:	NFPA 1001, 2019 Edition, 4.3.2
CONDITION:	Wearing full protective clothing, fire apparatus equipped with seat belts, radio headsets or other noise barriers.
COMPETENCE:	 Uses handholds or steps to mount apparatus. Secures safety devices as provided. Properly fasten seat belts. Don hearing protection if needed. Uses handholds or steps to dismount apparatus. Deploy traffic and scene control devices as appropriate.

FORCIBLE ENTRY

16- Demonstrate the proper care and maintenance of forcible entry tools and equipment.

- REFERENCE:NFPA 1001, 2019 Edition, 4.5.1CONDITION:Wearing gloves and eye protection, given cutting, prying, pulling,
or striking tools, chainsaw, ventilation fan (PPV), soap, water,
brush, & rags.COMPETENCE:• Proper carry for each tool.
• Protect self and others from sharp or pointed edges.
• Remove excess dirt with brush or hose.
• Wash tool with soap and water.
 - Inspect tool head and handle for damage.
 - Sharpen tool heads (per manufacture recommendations).
 - Dry tool and protect surface as per manufacture
 - recommendations.
- 17- Demonstrate or verbalize forcible entry and through-the-lock entry techniques for the following doors:

A. Swinging doors (stopped or rabbeted jamb).

REFERENCE:NFPA 1001, 2019 Edition, 4.3.4CONDITION:Wearing full protective clothing with eye protection (per NFPA 1500 Helmet face visor is not considered appropriate eye protection), appropriate forcible entry tool.COMPETENCE:• Select proper forcible entry tool(s).
• Proper carry of tool.
• Try door before prying.
• Correctly identify door type (stopped or rabbeted).
• Pry or force entry at or near lock.
• Force door correct direction.

FORCIBLE ENTRY

- 17- Cont: Demonstrate or verbalize forcible entry and through-the-lock entry techniques for the following doors:
- B. Sliding doors.

REFERENCE:	NFPA 1001, 2019 Edition, 4.3.4
CONDITION:	Wearing full protective clothing with eye protection (per NFPA 1500 Helmet face visor is not considered appropriate eye protection), appropriate forcible entry tool.
COMPETENCE:	 Select proper forcible entry tool(s).

- Select proper forcible entry tool(s).
 Proper carry of tool.
 - Try door before prying.
 - Iry door before prying.
 - Pry or force entry at lock.
 - Force door away from frame.

C. Overhead doors.

REFERENCE: NFPA 1001, 2019 Edition, 4.3.4

CONDITION: Wearing full protective clothing with eye protection (per NFPA 1500 Helmet face visor is not considered appropriate eye protection), appropriate forcible entry tool.

COMPETENCE: • Select proper forcible entry tool(s). • Proper carry of tool. • Try door before prying.

• Force entry by prying upward from bottom of door or remove door panel and open with inside latch.

• Door blocked open immediately after forcing entry.

18- Demonstrate or verbalize forcible entry and through-the-lock entry techniques for the following windows:

A. Sliding windows.

REFERENCE:	NFPA 1001, 2019 Edition, 4.3.4
CONDITION:	Wearing full protective clothing with eye protection (per NFPA 1500 Helmet face visor is not considered appropriate eye protection), appropriate forcible entry tool.
COMPETENCE:	 Select proper entry tool(s) Proper carry of tool. Try window before prying.

- Locate lock.
- Pry or force entry at proper location on window.

FORCIBLE ENTRY

- 18- Cont: Demonstrate or verbalize forcible entry and through-the-lock entry techniques for the following windows:
- B. Double hung windows.

REFERENCE:	NFPA 1001, 2019 Edition, 4.3.4
CONDITION:	Wearing full protective clothing with eye protection (per NFPA 1500 Helmet face visor is not considered appropriate eye protection), appropriate forcible entry tool.
COMPETENCE:	 Select proper entry tool(s) Proper carry of tool. Try window before prying.

- Locate lock.
- Pry or force entry at proper location on window.

C. Casement windows.

REFERENCE:	NFPA 1001, 2019 Edition, 4.3.4
CONDITION:	Wearing full protective clothing with eye protection (per NFPA 1500 Helmet face visor is not considered appropriate eye protection), appropriate forcible entry tool.
COMPETENCE:	 Select proper entry tool(s). Proper carry of tool. Cut screen in same area. Break lowest pane of glass. Unlock and operate window graph.

- Unlock and operate window crank.Completely remove screen.
- Completely remove soreen.
- **19-** Demonstrate or verbalize forcible entry for the following exterior walls:
- A. Masonry.

REFERENCE:	NFPA 1001, 2019 Edition, 4.3.4
CONDITION:	Wearing full protective clothing with eye protection (per NFPA 1500 Helmet face visor is not considered appropriate eye protection), appropriate forcible entry tool.
COMPETENCE:	 Select proper entry tool(s). Proper carry of tool. Correctly use tool(s) to force entry. Identify possible hazards associated with breaching wall.

FORCIBLE ENTRY

19- Cont: Demonstrate or verbalize forcible entry for the following exterior walls:

B. Metal.

REFERENCE:	NFPA 1001, 2019 Edition, 4.3.4
CONDITION:	Wearing full protective clothing with eye protection (per NFPA 1500 Helmet face visor is not considered appropriate eye protection), appropriate forcible entry tool.

- COMPETENCE: Select proper saw or entry tool.
 - Proper carry of tool.
 - Find and mark studs or supports.
 - Cut along studs with saw or tool.
 - Identify possible hazards associated with breaching wall.
- C. Wood.

REFERENCE:	NFPA 1001, 2019 Edition, 4.3.4
CONDITION:	Wearing full protective clothing with eye protection (per NFPA 1500 Helmet face visor is not considered appropriate eye protection), appropriate forcible entry tool.
COMPETENCE:	 Select proper entry tool(s). Proper carry of tool. Remove exterior covering. Sound for studs or supports. Cut along studs

- Cut along studs.
- Identify possible hazards associated with breaching wall.

<u>SAFETY</u>

20- Establish and operate in work area at an emergency scene.

REFERENCE:	NFPA 1001, 2019 Edition, 4.3.3
CONDITION:	Given an emergency scene, (roadway, structure fire, vehicle fire) wearing full PPE, safety vest if operating on roadway, traffic and scene control devices and an assignment.
COMPETENCE:	 Don Proper PPE prior to operating on scene. Dismount apparatus in safe manner.

- Establish safety zones as directed by IC.
- Operate at emergency scene within safety zones.

<u>SAFETY</u>

21- Demonstrate the use of SCBA to exit through a restricted passage.

REFERENCE:	NFPA 1001, 2019 Edition, 5.3.3, 4.3.9
CONDITION:	Wearing full protective clothing, SCBA, restricted passage where firefighter cannot pass without a low profile.
COMPETENCE:	 Loosen SCBA backpack (Leave facepiece on). Move SCBA backpack to side of firefighter. Enter restricted passage. Tighten SCBA backpack after through passage.

- 22- Demonstrate techniques for action when trapped or disoriented in a fire or hostile situation:
- A. Search for an exit using hose line.

REFERENCE:	NFPA 1001, 2019 Edition, 4.3.3, 4.3.5
CONDITION:	Wearing full protective clothing, SCBA (SCBA facepiece covered), 150 ft. of 1 1/2" or larger hose with nozzle attached, appropriate size room, and a 2-Firefighter team.
COMPETENCE:	 Call for help. Communicate to team member's actions, problems or needs for assistance. Activate PASS device (if used by department). Search for and locate hose, find coupling. Use hose and follow to safety using male coupling as a guide. Maintain contact with team member(s) verbally or physically. Exit hazardous area before exhausting air supply as a team.

B. Search for an exit using a wall.

REFERENCE:	NFPA 1001, 2019 Edition, 4.3.3, 4.3.5
CONDITION:	Wearing full protective clothing, SCBA (SCBA facepiece covered), appropriate size room, and a 2-Firefighter team.
COMPETENCE:	 Call for help. Communicate to team members actions, problems or needs for assistance. Activate PASS device (if used by department). Sourch for woll

- · Search for wall.
- Find wall and follow to safety using right or left-hand technique.
- Maintain contact with team member(s)verbally or physically.
- Exit hazardous area before exhausting air supply as a team.

LADDERS

24-

23- Identify the Parts of a Ladder.

REFERENCE:	NFPA 1001, 2019 Edition, 4.3.6
CONDITION:	Wearing full protective clothing and given an extension ladder.
COMPETENCE:	 Identify the Beam Identify the Bed Section Identify the Heel, Foot, Base, or Butt Identify the Fly Section Identify the Cleat, Shoes, or Butt Plates Identify the Dogs, Pawls, Rung Locks, or Ladder Locks Identify the Halyard Identify the Guides or Channels Identify the Sensor Labels Identify the Hooks (Roof Ladder) Identify the Rungs Identify the Rails Identify the Stops
Demonstrate the pro	per carry, position, raise, and lower of a roof ladder.
REFERENCE:	NFPA 1001, 2019 Edition, 4.3.6
CONDITION:	Wearing full protective clothing, a roof ladder, and starting from a designated point.
COMPETENCE:	 Lift ladder with legs (not back) to carry position. Carry ladder correctly (tip or heel forward according to ladder type). Check for overhead obstructions (must verbalize). Determine structure stability (must verbalize). Butt and raise ladder to proper position. Check climbing angle. Lower ladder to ground.
Demonstrate the pro	per carry, position, raise and lower of 24 ft, or 35 ft, extension

25- Demonstrate the proper carry, position, raise and lower of 24 ft. or 35 ft. extension ladder.

REFERENCE: NFPA 1001, 2019 Edition, 4.3.6

CONDITION: Wearing full protective clothing, a 24 ft. (2-firefighter team) or 35 ft. (4-firefighter team) ladder, appropriate number of personnel, and starting from a designated point.

COMPETENCE: • Leader gives prepatory commands.

- Team lifts with legs.
- Proper carry to structure.
- Check for overhead obstructions (must verbalize).
- Determine structure stability (must verbalize).
- Raise fly section to proper height.
- Determine locks are engaged (must verbalize).
- Tie off halyard.
- Check climbing angle.
- Lower ladder to ground.

LADDERS

27-

28-

26- Demonstrate procedure for climbing, working, and descending from extension or aerial ladder with a tool, (with safety harness for aerial ladder).

REFERENCE:	NFPA 1001, 2019 Edition, 4.3.6
CONDITION:	Wearing full protective clothing, axe, extension or aerial ladder (safety harness for aerial ladder) and starting from a designated point.
SAFETY ALERT:	NEVER USE LEG LOCK ON AERIAL LADDER. EXTENSION LADDER MUST BE HEELED BY SECOND FIREFIGHTER OR TIED OFF.
COMPETENCE:	 Check climbing angle of ladder. Climb with arms straight, body perpendicular to the ground. Climb smoothly and rhythmically. Maintain three points of contact with ladder while climbing. Carry tool properly. Lock-in around rung or use safety harness. Lock-in on opposite side from the working side.
Demonstrate bringing	a victim down a ladder from second story window or roof.
REFERENCE:	NFPA 1001, 2019 Edition, 4.3.6
CONDITION:	Wearing full protective clothing, extension ladder, and victim: conscious or unconscious.
SAFETY ALERT:	EXTENSION LADDER MUST BE HEELED BY SECOND FIREFIGHTER OR TIED OFF. SAFETY LINE OR HARNESS ON VICTIM OR USE RESCUE MANIKIN
COMPETENCE:	 Ensure tip of ladder placed correctly for rescue (must verbalize). Proper carry of victim (conscious or unconscious).
Demonstrate deploym	nent of a roof ladder on a pitched roof.
REFERENCE:	NFPA 1001, 2019 Edition, 4.3.6
CONDITION:	Wearing full protective clothing, roof ladder, extension ladder and 2-Firefighter team. (Begin with extension ladder placed on building).
SAFETY ALERT:	EXTENSION LADDER MUST BE HEELED BY SECOND FIREFIGHTER OR TIED OFF.
COMPETENCE:	 Raise roof ladder and place against extension ladder or roof. Properly climb extension ladder. Raise roof ladder with hooks open and facing away from firefighter on extension ladder. Carry roof ladder to the roofline and lock-in. Slide roof ladder up roof.

• Ensure hooks are securely grabbing peak of roof.

LADDERS

31-

29- Demonstrate inspection, maintenance, and cleaning procedures for ground and/or aerial ladders.

REFERENCE:	NFPA 1001, 2019 Edition, 4.5.1
CONDITION:	Given an extension ladder or a ladder on an aerial apparatus, soap, water, brush, rags, and 2-Firefighter team.
COMPETENCY:	 Wash ladder with water, soap, brush and then dry ladder. Check rungs for looseness, cracks, dents, or unusual wear. Check all bolts, rivets, and welds for looseness. Check beams, trusses, and truss blocks for damage. Check all braces, slides, stops, locks. Check pulleys and halyards. Check heat sensor labels for color change. Mark any defects found.

• Check for smooth operation by raising and lowering ladder.

HOSE, NOZZLES, APPLIANCES

30- Demonstrate proper set-up of a Master stream (300 gpm or greater).

REFERENCE:	NFPA 1001, 2019 Edition, 4.3.8
CONDITION:	Wearing protective clothing, water supply, master stream appliance, 100 feet 2 1/2" hose or larger, 2-Firefighter team.
COMPETENCE:	 Set up appliance. Connect hose line from apparatus to appliance. Signal for water. Exercise safety as hose lines charge. Adjust stream of appliance once water is at nozzle. Flow water.
Demonstrate the prop	er method for extending a charged hose line.
REFERENCE:	NFPA 1001, 2019 Edition, 4.3.10
CONDITION:	Wearing full protective clothing, 150 ft. of 1 1/2" or larger hose, hose clamp, nozzle, 2-Firefighter team.
COMPETENCE:	 Clamp hose approx. 3 feet behind nozzle, remove nozzle. Add 50' section of hose. Replace nozzle and charge hoseline slowly.

32- Demonstrate the proper method for replacing a burst section of hose.

REFERENCE:	NFPA 1001, 2019 Edition, 4.3.10
CONDITION:	Wearing full protective clothing, 150 ft. of 1 1/2" or larger hose, hose clamp, nozzle, 2-Firefighter team.
COMPETENCE:	 Clamp hose approx. 3 feet behind coupling. Drain hose at nozzle. Replace 2 sections for one burst section. Remove hose clamp and charge hoseline slowly.

33- Demonstrate coupling and uncoupling hose using the following:

A. Foot-Tilt method.

REFERENCE:	NFPA 1001, 2019 Edition, 4.3.10
CONDITION:	With gloves, 100 ft. of 2 1/2" or larger hose.
COMPETENCE:	 Place foot behind male end of hose and apply pressure to tilt male coupling. Connect female end to male end.

B. Two-Firefighter method.

REFERENCE:	NFPA 1001, 2019 Edition, 4.3.10
CONDITION:	With gloves, 100 ft. of 1 1/2" or larger hose.
COMPETENCE:	 One firefighter holds male coupling and one firefighter holds female coupling. Firefighter holding female coupling connects hose to male coupling using the Higbee indicator as a guide.

34- Advance a charged and uncharged attack line from a pumper, for the following:

A. For ground level fire attack (structural, ground cover, and vehicle).

REFERENCE:	NFPA 1001, 2019 Edition, 4.3.10
CONDITION:	Wearing full protective clothing, SCBA, 150 feet of 1 1/2" hose or larger, nozzle.

COMPETENCE:
Correctly unload hose from apparatus.
Advance hose to attack position.
Signal for water.
Open nozzle to bleed air from attack line and check stream pattern.

- 34- Cont: Advance a charged and uncharged attack line from a pumper, for the following:
- B. Up a ladder to second floor window or roof.

REFERENCE:	NFPA 1001, 2019 Edition, 4.3.10
CONDITION:	Wearing full protective clothing, SCBA, 2-Firefighter team, 150 feet of 1 1/2" hose or larger, nozzle, extension ladder hose straps or webbing.
COMPETENCE:	 Correctly unload hose from apparatus. Advance hose up the ladder. Secure hose to ladder with hose straps or webbing.

· Signal for water.

• Open nozzle to bleed air from attack line and check stream pattern.

C. Up/down an inside/outside stairway to upper/lower floors.

REFERENCE:	NFPA 1001, 2019 Edition, 4.3.10
CONDITION:	Wearing full protective clothing, SCBA, 150 feet of 1 1/2" hose or larger, nozzle and 2-Firefighter team.
COMPETENCE:	 Correctly unload hose from apparatus. Advance to door, feel door for heat. Signal for water. Open nozzle to bleed air from attack line and check stream pattern. Advance up or down 2 flights of stairs. Lay hose against outside wall.

35- Demonstrate how to connect to a standpipe and advance a hoseline from the standpipe.

REFERENCE:	NFPA 1001, 2019 Edition, 4.3.10
CONDITION:	Wearing full protective clothing, 100 feet of 1 1/2" or larger hose, 2-Firefighter team and nozzle.
COMPETENCE:	 Advance to standpipe with needed equipment. Connect to standpipe at connection below fire floor. Properly position hose line in stairwell. Advance the entire hose length, avoiding kinks. Signal for water. Open nozzle to bleed air from attack line and check stream pattern.

36- Demonstrate the following hose carries:

A. Single section drain and carry.

REFERENCE:	NFPA 1001, 2019 Edition, 4.3.10
CONDITION:	Wearing full protective clothing, 50 ft. of 1 1/2" or larger hose.
COMPETENCE:	 Pick-up coupling allowing water to drain. Place coupling in front of body with hose loop over shoulder. Layer hose on shoulder. Hose controlled and secured.

B. Accordion shoulder carry.

REFERENCE:	NFPA 1001, 2019 Edition, 4.3.10
CONDITION:	Wearing full protective clothing, 50 ft. of 1 1/2" or larger hose.
COMPETENCE:	 Fold hose on ground. Line up folds and couplings. Lift hose to shoulder using legs. Hose controlled and secured.

37- Demonstrate the following hose loads:

A. Load supply hose lines on fire apparatus using the Flat or Accordion hose loads.

REFERENCE:	NFPA 1001, 2019 Edition, 4.5.2,
CONDITION:	With gloves, 150 feet of 2 1/2" or larger hose, 3-Firefighter team.
COMPETENCE:	Layer hose in hose bed.Use Dutchman where appropriate.

B. Load attack hose lines on fire apparatus using the flat, triple fold or Minuteman hose loads.

REFERENCE:	NFPA 1001, 2019 Edition, 4.5.2,
CONDITION:	With gloves, 150 feet of 1 1/2" or 1 3/4" hose, 3-Firefighter team.
COMPETENCE:	 Attach female coupling to discharge. Layer hose in hose bed. Use Dutchman where appropriate.

• Finish load with nozzle in correct location and secured.

38- Demonstrate the following hose rolls:

A. Straight roll.

Β.

REFERENCE:	NFPA 1001, 2019 Edition, 4.5.2
CONDITION:	With gloves, 50 feet of 1 1/2" hose or larger.
COMPETENCE:	 Roll hose with male coupling in the center. Lay completed roll on ground, tamp protruding coils.
Donut roll.	
REFERENCE:	NFPA 1001, 2019 Edition, 4.5.2

COMPETENCE:	 Roll hose with male coupling inside roll and female coupling
	approximately 3' ahead of male coupling.
	 Lay completed roll on ground, tamp protruding coils.

39- Demonstrate the procedures for cleaning, inspecting and maintaining: Fire hose and couplings.

REFERENCE:	NFPA 1001, 2019 Edition, 4.5.2
CONDITION:	Fire hose, soap, water, brush or hose washing and drying equipment.
COMPETENCY:	 Wash hose using clear water and a brush, if required use mild soap. Rinse with clear water. Wash couplings with clear water and a brush. Inspect hose for mechanical, thermal, or chemical damage. Inspect couplings for damage. Remove gasket from female coupling and check for cracks. Reinstall gasket in female coupling. Check male threads for damage by threading in to female coupling. Mark and record any damage found if necessary remove from service.

SEARCH AND RESCUE

- 40- Demonstrate proper techniques while conducting a search for a victim in a structure (with or without hose line or safety rope) and remove victim to safe area.
 - REFERENCE:NFPA 1001, 2019 Edition, 4.3.9CONDITION:Wearing full protective clothing, SCBA (covered facepiece),
forcible entry tool, 2-Firefighter team, 300 sq. ft. room.COMPETENCE:• Search on hands and knees.
• Use right or left hand search pattern.
 - Call out for victim.
 - Pause occasionally to listen for sounds.
 - Locate victim and communicate it to command.
 - Remove victim to safe area using appropriate drag or carry.
 - Team integrity is maintained during search.

41- Demonstrate proper rescue procedures for the following:

A. Move a victim 40 feet using the extremities carry.

- REFERENCE:NFPA 1001, 2019 Edition, 4.3.9CONDITION:Wearing full protective clothing, 2-Firefighter team, and Civilian
- victim. COMPETENCE: • Firefighter at head gives commands. • Lift with legs.
 - Perform correct carry.
 - Move victim 40 feet.
- B. Move an unconscious firefighter with or without functioning SCBA, 40 feet using the coat drag, webbing etc. or SCBA
 - REFERENCE: NFPA 1001, 2019 Edition, 4.3.9
 - CONDITION: Wearing full protective clothing, 2-Firefighter team and firefighter victim.
 - COMPETENCE: Place firefighter face-up.
 - Grasp fire coat by collar, webbing etc. or SCBA.
 - Work as a team to move firefighter to safe area.
 - Move victim 40 feet

C. Move an unconscious victim 40 feet using the blanket drag.

REFERENCE: NFPA 1001, 2019 Edition, 4.3.9

CONDITION: Wearing full protective clothing, 2-Firefighter team, victim and blanket.

- COMPETENCE:
 Place victim face-up.
 Roll victim to one side and place blanket under victim.
 Roll victim opposite side and pull blanket to other side of victim.
 Work as a team, grasp blanket near victim's head and move to
 - safe area.
 - Move victim 40 feet.

VENTILATION

42- Demonstrate determining the integrity of a roof by sounding.

REFERENCE:	NFPA 1001, 2019 Edition, 4.3.12
CONDITION:	Wearing full protective clothing, axe, ladder, rope.
COMPETENCE:	 Sound roof before stepping on. Stay on roof supports. Sound roof to locate supports. Mark location of rafters or solid supports.

43- Demonstrate or verbalize procedures for breaking window or door glass and removing obstructions, from ground level and while working from a ladder.

A. Ground level.

REFERENCE:	NFPA 1001, 2019 Edition, 4.3.11
CONDITION:	Wearing full protective clothing, pike pole or axe.
COMPETENCY:	 Stand to windward side of glass pane.

- Strike with tool at top of pane.
- Keep hands above point of impact.
- Stand at 45 degree angle to window/door if using pike pole.
- Clear all glass from frame or track.
- Remove screens and drapes.

B. From ladder.

- REFERENCE: NFPA 1001, 2019 Edition, 4.3.11
- CONDITION: Wearing full protective clothing, ladder, pike pole or axe.

SAFETY: LADDER HEELED BY SECOND FIREFIGHTER

COMPETENCY:

- Place ladder to windward side of window.
- Correctly lock-in on ladder.
- Strike with tool at top of pane.
- Keep hands above point of impact.
- Clear all glass from frame or track.
- Remove screens and drapes.

VENTILATION

- 44- Demonstrate opening a ventilation hole for all of the following for vertical ventilation.
- A. Pitched or Flat roof.

REFERENCE:	NFPA 1001, 2019 Edition, 4.3.12
CONDITION:	Wearing full protective clothing, fire axe, power saw, pike pole, roof ladder, and 3-Firefighter team.
COMPETENCE:	 Proper use of roof ladder (with wind at firefighters back or side). Use spotter for safety. Sound roof and mark rafters or structural supports. Remove built up roof material. Correctly open ventilation hole. Use pike pole to push down ceiling and remove any barriers. Exit roof area once ventilation hole is completed.

B. Floor.

45.

REFERENCE:	NFPA 1001, 2019 Edition, 4.3.12
CONDITION:	Wearing full protective clothing, chain saw, circular saw, or axe, and pike pole 2-Firefighter team.
	 Sound floor for structural supports. Correctly open ventilation hole. Use pike pole to remove any barriers. Exit once ventilation hole is completed.
circletare acting mega	
REFERENCE:	NFPA 1001, 2019 Edition, 4.3.11
CONDITION:	Wearing full protective clothing, SCBA, 2-Firefighter team, smoke ejector.
COMPETENCE:	Place smoke ejector to exhaust in the same direction as the natural wind

- natural wind
- Seal around ejector to eliminate air churning
- Open windows and doors on windward side of structure to aid in ventilation process
- Keep airflow in as straight a line as possible
- Remove all obstacles to airflow
- Start smoke ejector

VENTILATION

46. Demonstrate the set up of a high volume blower fan in a doorway for "positive pressure" ventilation of a structure.

REFERENCE:	NFPA 1001, 2019 Edition, 4.3.11
CONDITION:	Wearing full protective clothing, SCBA, 2-Firefighter team, positive-pressure ventilation blower/fan.
COMPETENCY:	 Start positive pressure blower. Set blower so that the cone of air from the blower completely covers the door opening. Set blower so placement does not interfere with entry & exit of firefighters from the building. Exhaust opening should be 75 to 150 percent as large as the entry opening. Open interior doors systematically to maintain positive pressure in the structure.

OVERHAUL OPERATIONS

47- Demonstrate or verbalize search and exposure of hidden fires in: walls, ceilings, and floors.

REFERENCE:	NFPA 1001, 2019 Edition, 4.3.13
CONDITION:	Wearing full protective clothing, appropriate tools, flashlight, hose line or water extinguisher.
COMPETENCE:	 Search for hidden fires using; sight, touch, sound, or electronic sensors. Feel for heat with the back of ungloved hand. With appropriate tool open walls, ceilings, and floors to expose hidden fire. Expose void spaces without compromising structural integrity. Use water as needed to extinguish hidden fires as found.

• Fire cause evidence is preserved

SALVAGE OPERATIONS

48- Demonstrate the proper folds and rolls for salvage covers:

A. Fold or roll a salvage cover for one-firefighter spread.

REFERENCE:	NFPA 1001, 2019 Edition, 4.3.14	
CONDITION:	Wearing full protective clothing, AHJ approved salvage cover, and a 2-Firefighter team.	
COMPETENCE:	 Fold cover to reduce size. Fold with finish side out. Finish cover by rolling or folding. 	
B. Fold or roll a salvage cover for two-firefighter spread.		
REFERENCE:	NFPA 1001, 2019 Edition, 4.3.14	
CONDITION:	Wearing full protective clothing, AHJ approved salvage cover, and a 2-Firefighter team	
COMPETENCE:	Fold cover to reduce size.	

• Finish cover by folding for two-firefighter spread.

49- Demonstrate one-firefighter and two-firefighter deployment of a salvage cover.

A. One-firefighter deployment.

REFERENCE:	NFPA 1001, 2019 Edition, 4.3.14	
CONDITION:	Wearing full protective clothing, AHJ approved salvage cover.	
COMPETENCE:	 Stack (cluster) objects to be covered. Lay cover in the center of objects to be covered. Unfold or unroll cover over all objects. Snap cover open at ends. Tuck cover in at bottom. 	
B. Two-firefighter deployment (Balloon Throw).		
REFERENCE:	NFPA 1001, 2019 Edition, 4.3.14	
CONDITION:	Wearing full protective clothing, AHJ approved salvage cover and 2-Firefighter team.	
COMPETENCE:	 Stack (cluster) objects to be covered. Stretch the cover along one side of the object to be covered. Make several accordion folds with inside hand. Pull the cover tight and throw, pocketing as much air as possible. As a team float the cover over the object to be covered. 	

• Guide into position and tuck in at bottom.

SALVAGE OPERATIONS

- 50- Demonstrate the proper construction of a water chute (minimum 10 ft.) down a stairwell or out a window.
 - REFERENCE: NFPA 1001, 2019 Edition, 4.3.14
 - CONDITION: Wearing full protective clothing, salvage cover, attic ladder or 2pike poles and 2-Firefighter team.
 - COMPETENCE: • Open salvage cover. • Roll salvage cover edges over pike poles and turn over to create water chute. • Adjust water chute on ladder for water removal out window. • Remove water from structure.

51- Demonstrate the proper construction of a catchall.

- REFERENCE:NFPA 1001, 2019 Edition, 4.3.14CONDITION:Wearing full protective clothing, AHJ approved salvage cover
and 2-Firefighter team.
- COMPETENCE: • Open salvage cover. • Fold corners inward at 45 degree. • Roll sides inward approximately 3'.
 - Tuck the end roll under the side roll to lock.

52- Demonstrate the covering or closing of building openings including: doors, windows, floors, and roofs.

- REFERENCE:NFPA 1001, 2019 Edition, 4.3.14CONDITION:Wearing full protective clothing, appropriate materials to cover
openings, 2-Firefighter team
- COMPETENCE:
 Select correct material to cover openings.
 Use sufficient amount of material to cover the opening completely.
 Tack edges of material down completely to keep weather out.
- 53- Separate, remove, and relocate charred material from un-charred material while protecting the area of fire origin for determination of fire cause.

REFERENCE:	NFPA 1001, 2019 Edition, 4.3.14
CONDITION:	Wearing full protective clothing, appropriate tools and equipment, flashlight, hoseline or water extinguisher, two firefighter team.
COMPETENCE:	 Separate charred from un-charred material. Extinguish any smoldering material. Remove charred material to safe area. Preserve any evidence found by leaving where found.

SALVAGE OPERATIONS

54- Demonstrate stopping the flow of water from a discharging sprinkler head, using a wedge or stopper.

REFERENCE:	NFPA 1001, 2019 Edition, 4.3.14
CONDITION:	Wearing full protective clothing, wedges or stopper.
COMPETENCE:	Select appropriate tool.Stop sprinkler flow.

55- Operate a main control valve on an automatic sprinkler system from "open" to "closed" and then back to "open".

REFERENCE:	NFPA 1001, 2019 Edition, 4.3.14
CONDITION:	Wearing full protective clothing.
COMPETENCE:	 Identify main control valve Close valve fully Open valve fully

56- Demonstrate the procedure of inspection, cleaning, and maintaining salvage covers.

REFERENCE:	NFPA 1001, 2019 Edition, 4.3.14
CONDITION:	Salvage cover, soap and water, brushes or brooms.
COMPETENCE:	 Demonstrate washing and drying salvage cover. Inspect cover for tears or holes. Mark holes if found and describe repair procedures.

WATER SUPPLY

- 57- Demonstrate hydrant-to-pumper hose connections for a:
- A. Forward hose lay using departmental Policy and Procedures.

REFERENCE:	NFPA 1001, 2019 Edition, 4.3.15
CONDITION:	Wearing full protective clothing, 2 1/2" or larger supply hose, gate valves, spanner wrenches and hydrant wrench.
COMPETENCE:	 Select correct equipment to connect to hydrant. Loop hose around hydrant, secure hose (stand on correct side of hydrant). Signal apparatus to proceed. Connect hydrant gate valves. Open hydrant completely, flush, (open gradually to prevent water hammer). Charge hoseline (slowly) when signal is given. Shut hydrant down slowly to prevent water hammer and check drain.

WATER SUPPLY

- 57- Cont: Demonstrate hydrant-to-pumper hose connections for a:
- B. Reverse hose lay using departmental Policy and Procedures.

REFERENCE: NFPA 1001, 2019 Edition, 4.3.15

- CONDITION: Wearing full protective clothing, 2 1/2" or larger supply hose, gate valves, spanner wrenches hydrant wrench, Wye-gate, reducers, 1 1/2" or larger attack line with nozzle, 2-firefighter team, or 3-firefighter team with 3" hose.
- COMPETENCE:
 Select equipment needed to place one attack hose in service and drop at scene. (Attack hose 150' in length).
 Remove and ground 50' of supply hose from apparatus.
 Kneel on hose and signal apparatus to proceed.

• Connect attack hose to supply hose, and signal for water when ready.

- Charge hoseline, and open nozzle.
- 58- Demonstrate a hand lay of 300 feet of supply line, 2 1/2" or larger from a pumper to a water source.
 - REFERENCE:NFPA 1001, 2019 Edition, 4.3.15CONDITION:Wearing full protective clothing, appropriate equipment to
connect to hydrant, 300 ft of supply hose, 3-Firefighter team.
 - COMPETENCE: Shoulder load 50 ' of hose from hose bed, drag 50' (per firefighter).
 - Maintain equal distance between firefighters.
 - Lay entire length with no kinks or tangles.
 - · Connect to hydrant.
- 59- Demonstrate the assembly and connecting of the equipment necessary for drafting from a static water supply source.

REFERENCE:	NFPA 1001, 2019 Edition, 4.3.15
CONDITION:	Wearing full protective clothing, 2 sections of 2 1/2" or larger hard suction hose, appropriate adapters, tools, and roof ladder 2-Firefighter team.
COMPETENCE:	 Fasten rope to strainer to aid in handling hard suction hose. Couple strainer to hard suction hose. Couple the two sections of hard suction hose together, taking care not to get dirt in coupling. Connect completed hose to apparatus. Use ladder to place hard hose on to keep out of dirt and mud. Uses rubber mallet to ensure air-tight connections.

WATER SUPPLY

60- Demonstrate the assembly and connecting of the equipment necessary for drafting from a portable water tank.

REFERENCE:NFPA 1001, 2019 Edition, 4.3.15CONDITION:Wearing full protective clothing, 2 sections of 2 1/2" or larger
hard suction hose, appropriate adapters and tools, portable tank,
2-Firefighter team.COMPETENCE:• Set up portable water tank.
• Fasten rope to strainer to aid in handling hard suction hose.
• Couple strainer to hard suction hose.
• Couple the two sections of hard suction hose together, taking
care not to get dirt in coupling.
• Connect completed hose to apparatus.
• Uses rubber mallet to ensure an air-tight connection.

PORTABLE FIRE EXTINGUISHERS

61- Demonstrate the use of portable fire extinguishers on Class A, Class B, and Class C fires.

REFERENCE:	NFPA 1001, 2019 Edition, 4.3.16
CONDITION:	Wearing full protective clothing including eye protection, class A- B-C portable extinguisher.
COMPETENCE:	 Select correct extinguisher for type of fire. Check pressure gauge. Pull pin and squeeze handle to test extinguisher. Approach fire upwind/upgrade. Correctly extinguish fire by sweeping the nozzle back and forth at the base of the flames.

FIREGROUND SUPPORT ACTIVITIES

62- Demonstrate safety procedures when using fire service lighting equipment.

REFERENCE:	NFPA 1001, 2019 Edition, 4.3.17
CONDITION:	Wearing full protective clothing, power supply (mounted or portable), lights, cords, connectors, ground-fault interrupter (GFI).
COMPETENCE:	 Start power supply. Reset ground-fault interrupter (GFI) if necessary. Extend cord and light (if applicable). Illuminate light.

FIREGROUND SUPPORT ACTIVITIES

63- Demonstrate or verbalize shutting off utility services to a building:

A. Shut off propane tank or natural gas valve.

REFERENCE:	NFPA 1001, 2019 Edition, 4.3.18
CONDITION:	Wearing full protective clothing, appropriate tool for natural gas or propane tank.
COMPETENCE:	Select correct tool.Turn valve(s) to the off position.
B. Secure power	to structure by shutting off main power breaker.
REFERENCE:	NFPA 1001, 2019 Edition, 4.3.18

CONDITION: Wearing full protective clothing.

COMPETENCY:	 Select correct breaker.
	Switch breaker to the off position.

64- Demonstrate the ability to operate an air monitoring instrument:

REFERENCE:	NFPA 1001, 2019 Edition, 4.3.21
CONDITION:	Given an air monitor and an assignment or task, the candidate shall demonstrate the ability to operate the device and recognize alarms and take actions to mitigate the hazard.
COMPETENCE:	 Demonstrate the ability to operate the device. Ensure all responders are wearing appropriate PPE. Ensure all responders are wearing appropriate PPE. Inspect monitor to ensure that it is serviceable. Perform a bump test. Perform a "fresh air" calibration prior to entry. Monitor the area per AHJ SOPs. If the monitor alarms, identify the cause for the alarm. When complete, turn off, decontaminate and place in service. Complete required reports/supporting documentation.

PERSONAL PROTECTIVE EQUIPMENT

Skill 1: Demonstrate the care, inspection, and maintenance of protective clothing assigned or available for use. NFPA 1001 2019 Edition 4.1.2

CONDITION: Given helmet with eye shield (per NFPA 1500 helmet face visor is not considered appropriate eye protection), Hood, Boots, Gloves, Coat, & Pants.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

		<u>1st. Att</u>	<u>. 2nd Att.</u>
		Y N	YN
1. Inspect all equipment for c	lamage		
2. Remove dirt, chemicals, o	il or other compounds		
from protective clothing.			
3. Inspect helmet and visor fe	•		
 Inspect suspenders for da Describe proper cleaning in 	•		
(Manufacturer recommended	l or department SOP).		
PERFORMANCE RATING (ON THIS SKILL:	PASS	FAIL
	First Attempt		
	Second Attempt		
Evaluator Comments:			
Evaluator #1:			
(Please Prin	t)		
Evaluator #2:			
(Please Prin	t)		
Notice to Evaluators: Cand	idate must sign for 2nd attem	ot failures	By this

Notice to Evaluators: Candidate must sign for **2nd attempt failures**. By this signature the candidate is notified that he/she has failed this skill and will be required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of **this skill** plus **one additional skill** from this same area of the standard.

Candidate's Signature:_____

PERSONAL PROTECTIVE EQUIPMENT

- **Skill 2:** Demonstrate donning and doffing structural firefighter protective clothing. NFPA 1001 2019 Edition 4.1.2
- **CONDITION:** Given helmet with eye shield (per NFPA 1500 helmet face visor is not considered appropriate eye protection), Hood, Boots, Gloves, Coat, & Pants,

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

	<u>1st. Att.</u>	<u>2nd Att.</u>
	ΥN	ΥN
1. Don Hood (hood maybe rolled down around collar of coat) 🗆 🗆	
2. Don and fasten all closures on pant/boot sand coat.		
3. Collar turned up on coat.		
4. Don helmet and tighten chin strap, helmet ear		
flaps down.		
5. Don gloves.		
6. Doff protective clothing and place back in service.		
PERFORMANCE RATING ON THIS SKILL:	<u>PASS</u>	<u>FAIL</u>
First Attempt		
Second Attempt		
Evaluator Comments:		
Evaluator #1:		
(Please Print)		
Evaluator #2:		
(Please Print)		
Notice to Evaluators: Candidate must sign for 2nd attemp	t failuree	By this

Notice to Evaluators: Candidate must sign for **2nd attempt failures**. By this signature the candidate is notified that he/she has failed this skill and will be required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of **this skill** plus **one additional skill** from this same area of the standard.

Candidate's Signature:

<u>ROPES</u>

- Skill 3: Demonstrate the hoisting of the following tools: fire axe, pike pole, roof ladder, & hose line (charged/dry). NFPA 1001 2019 Edition 4.1.2, 4.3.11b, 4.3.12b, 4.3.20
- **CONDITION:** Wearing full protective clothing, tool or equipment, minimum 25 ft. of rope.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

		<u>1st. Att.</u>	<u>2nd Att.</u>
 Select tool to be hoisted. Tie an appropriate knot for hoisting (Skill # 	1A-D) for	Y N	Y N
hoisting.			
3. Use "tag" line when directed.			
4. Hoist tool or equipment.			
	Attempt and Attempt	PASS	<u>FAIL</u>
Evaluator Comments:			
Evaluator #1:			
(Please Print)			
Evaluator #2:			
(Please Print)			
Notice to Evaluators: Candidate must sign f signature the candidate is notified that he/she	•		•

signature the candidate is notified that he/she has failed this skill and will be required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of **this skill** plus **one additional skill** from this same area of the standard.

Candidate's Signature:_____

ROPES

Skill 4A:	Demonstrate tying a Bowline around waist and/or around an
	object, with overhand safety. NFPA 1001 2019 Edition 4.1.2

CONDITION: Given a length of rope, object such as a pole or waist.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

		<u>1st. Att.</u>	2nd Att.
		ΥN	ΥN
1. Select correct length of rope.			
2. Tie correct knot with overhand safety	in correct position.		
PERFORMANCE RATING ON THIS S	KILL:	PASS	FAIL
	First Attempt		
	Second Attempt		
Evaluator Comments:			
Evaluator #1:			
(Please Print)			
Evaluator #2:			
(Please Print)			
Notice to Evaluators: Candidate must signature the candidate is notified that I required to take a 3rd and final attempt	he/she has failed this	skill and	will be

signature the candidate is notified that he/she has failed this skill and will be required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of **this skill** plus **one additional skill** from this same area of the standard.

Candidate's Signature:

ROPES

Skill 4B:	Demonstrate tying a Clove Hitch , running or loop method
	(with overhand safety). NFPA 1001 2019 Edition 4.1.2

CONDITION: Given a length of rope, object to place knot on.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

		<u>1st. Att.</u>	<u>2nd Att.</u>
		ΥΝ	YN
1. Select correct length of rope.			
2. Tie correct knot with overhand safety	in correct position.		
PERFORMANCE RATING ON THIS SH		PASS	FAIL
	First Attempt	\square	
	Second Attempt		
Evaluator Comments:			
Evaluator #1:			
(Please Print)			
Evaluator #2:			
(Please Print)			
<i>Notice to Evaluators:</i> Candidate must signature the candidate is notified that h	• •		•

signature the candidate is notified that he/she has failed this skill and will be required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of **this skill** plus **one additional skill** from this same area of the standard.

Candidate's Signature:

Skill 4C: Demonstrate tying a Figure Eight on a Bight, with overhand safety. NFPA 1001 2019 Edition 4.1.2

CONDITION: Given a length of rope.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

		<u>1st. Att.</u>	<u>2nd Att.</u>
		YN	YN
1. Select correct length of rope.			
2. Tie correct knot with overhand safety in	correct position.		
PERFORMANCE RATING ON THIS SKIL		<u>PASS</u>	<u>FAIL</u>
	rst Attempt		
Se	econd Attempt		
Evaluator Comments:			
Evaluator #1:			
(Please Print)			
Evaluator #2:			
(Please Print)			
<i>Notice to Evaluators:</i> Candidate must sig signature the candidate is notified that he/s			

signature the candidate is notified that he/she has failed this skill and will be required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of **this skill** plus **one additional skill** from this same area of the standard.

Skill 4D: Demonstrate tying a Figure eight follow through, with overhand safety. NFPA 1001 2019 Edition 4.1.2,

CONDITION: Given a length of rope, object to place knot on.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

		<u>1st. Att.</u>	<u>2nd Att.</u>
		ΥN	ΥN
1. Select correct length of rope.			
2. Tie correct knot with overhand safety i	n correct position.		
		DA00	
PERFORMANCE RATING ON THIS SK		PASS	<u>FAIL</u>
	First Attempt Second Attempt		
	Second Allempi		
Evaluator Comments:			
Evaluator #1:			
(Please Print)			
Evaluator #2:			
(Please Print)			
Notice to Evaluators: Candidate must s signature the candidate is notified that he			

signature the candidate is notified that he/she has failed this skill and will be required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of **this skill** plus **one additional skill** from this same area of the standard.

Skill 4E: Demonstrate tying a Becket or Sheet Bend, with overhand safety. NFPA 1001 2019 Edition 4.1.2

CONDITION: Given 2 pieces of rope of different diameter.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

	<u>1st. Att.</u>	2nd Att.
	ΥN	YN
1. Select correct length of rope in correct position.		
2. Larger rope should form the bight.		
3. Tie correct knot.		
PERFORMANCE RATING ON THIS SKILL:	<u>PASS</u>	<u>FAIL</u>
First Attempt		
Second Attempt		
Evaluator Comments:		
Evaluator #1:		
(Please Print)		
Evaluator #2:		
(Please Print)		
Notice to Evaluators: Candidate must sign for 2nd attem	pt failures	. By this

signature the candidate is notified that he/she has failed this skill and will be required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of **this skill** plus **one additional skill** from this same area of the standard.

<u>ROPES</u>

Skill 4F:	Demonstrate tying a Water knot , with overhand safety.
	NFPA 1001 2019, 4.1.2

CONDITION: Given 12 ft. X 1 inch tubular webbing.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

		<u>1st. Att</u>	2nd Att.
		ΥN	ΥN
1. Select correct length of webbing.			
2. Tie correct knots with overhand saf	fety in correct position.		
PERFORMANCE RATING ON THIS	SKILL:	PASS	FAIL
	First Attempt		
	Second Attempt		
Evaluator Comments:			
Evaluator #1:			
(Please Print)			
Evaluator #2:			
(Please Print)			
<i>Notice to Evaluators:</i> Candidate must signature the candidate is notified that required to take a 3rd and final attemption.	t he/she has failed this	skill and	will be

Candidate's Signature:

same area of the standard.

Skill 5: Demonstrate inspecting, cleaning, and storing rope after use. NFPA 1001 2019, 4.1.2

CONDITION: Given rope, rope bag (if available) and cleaning supplies.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

		<u>1st. Att.</u>	<u>2nd Att.</u>
 Identify type of rope, life safety or utili Inspect rope for damage or wear. Wash rope using approved method (ver Dry rope using approved method (ver Bag or coil rope. Document use of rope and inspection 	verbalize). balize).	Y N	YN
PERFORMANCE RATING ON THIS SP	(ILL: First Attempt Second Attempt	PASS	<u>FAIL</u>
Evaluator Comments:			
Evaluator #1:			
(Please Print)			
Evaluator #2:			
(Please Print)			
<i>Notice to Evaluators:</i> Candidate must signature the candidate is notified that h required to take a 3rd and final attempt, date. The 3rd attempt will consist of this	e/she has failed t no sooner than 3	this skill and 0 days from	will be today's

Candidate's Signature:

same area of the standard.

Skill 6: Demonstrate receiving a report of a fire or emergency situation from the public (telephone) and initiate appropriate action. NFPA 1001 2019, 4.2.1

CONDITION: Given a fire or emergency scenario.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

		<u>1st. Att.</u>	<u>2nd Att.</u>
		ΥN	ΥN
1. Identify self.			
2. Record time of call.			
3. Record type and address of incider	it.		
4. Record callers name and call back	number.		
5. Ask questions for additional information	ation.		
6. Hang up after caller.			
PERFORMANCE RATING ON THIS	SKILL:	PASS	FAIL
	First Attempt		
	Second Attempt		
Evaluator Comments:			
Evaluator #1:			
(Please Print)			
Evaluator #2:			
(Please Print)			
<i>Notice to Evaluators:</i> Candidate must signature the candidate is notified that			

signature the candidate is notified that he/she has failed this skill and will be required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of **this skill** plus **one additional skill** from this same area of the standard.

Skill 7: Demonstrate receiving a business or personal telephone call from the public. NFPA 1001 2019, 4.2.2

CONDITION: Given a scenario, following department SOP.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

		<u>1st. Att.</u>	<u>2nd Att.</u>
		ΥΝ	YN
1. Identify self.			
2. Record time of call.			
3. Record message.			
4. Record callers name and call back nun			
5. Ask questions for additional information	۱.		
6. Hang up after caller.			
PERFORMANCE RATING ON THIS SKI	LL:	PASS	FAIL
	First Attempt		
S	Second Attempt		
Evaluator Comments:			
Evaluator #1:			
(Please Print)			
Evaluator #2:			
(Please Print)			
Notice to Evaluators: Candidate must si			
signature the candidate is notified that he	/she has failed this	s skill and	will be
required to take a 3rd and final attempt, n		•	•
date. The 3rd attempt will consist of this s	skill plus one add	itional sk	ill from this
same area of the standard.			

Skill 8: Demonstrate the use of mobile and portable radio equipment for routine or emergency traffic. NFPA 1001 2019, 4.2.3

CONDITION: Given a mobile/portable radio equipment.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

		<u>1st. Att</u>	<u>. 2nd Att.</u>
 Turn on power. Set to correct channel. Adjust volume. Adjust squelch (if radio is equipped). Perform radio check (simulate). If emergency traffic, give EMERGENCY TRAFFIC signal over the air (simulated). 		Y N	Y N
PERFORMANCE RATING ON THIS	SKILL: First Attempt Second Attempt	PASS	FAIL
Evaluator Comments:			
Evaluator #1:			
(Please Print)			
Evaluator #2:			
(Please Print)			
Notice to Evaluators: Candidate mu	ust sign for 2nd attem	pt failures	By this

Notice to Evaluators: Candidate must sign for **2nd attempt failures**. By this signature the candidate is notified that he/she has failed this skill and will be required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of **this skill** plus **one additional skill** from this same area of the standard.

Skill 9: Demonstrate activating an emergency call for assistance. NFPA 1001 2019, 4.2.4

CONDITION: Given mobile/portable radio equipment and flashlight, wearing full protective clothing and SCBA in vision obscured conditions.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

	<u>1st. Att</u>	<u>. 2nd Att.</u>
	ΥN	ΥN
1. Identify need to declare "May Day".		
2. Announce "May Day, May Day, May Day" over		
communications channel.		
3. Provide Command with information (LUNAR).		
4. Activate PASS device.		
5. Move to safe location.		
6. Activate flashlight, pointed at ceiling.		
7. Conserve air supply		
PERFORMANCE RATING ON THIS SKILL:	PASS	<u>FAIL</u>
First Attempt Second Attempt		
Second Attempt		
Evaluator Comments:		
Evaluator #1:		
(Please Print)		
Evaluator #2:		
(Please Print)		
Notice to Evaluators: Candidate must sign for 2nd attem	pt failures	. Bv this

signature the candidate is notified that he/she has failed this skill and will be required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of **this skill** plus **one additional skill** from this same area of the standard.

- Skill 10: Identify and describe of each component of the Self-Container Breathing Apparatus (SCBA). NFPA 1001 2019, 4.3.1
- **CONDITION:** Given a Self-Container Breathing Apparatus as used by department.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

	<u>1st. Att.</u>	<u>2nd Att.</u>
1. Backpack/harness.	Y N	Y N
 2. Air cylinder: cylinder, valve, and pressure gauge. 3. Regulator assembly: high-pressure hose, low pressure alarm, main line valve, emergency by-pass valve, 		
secondary gauges. 4. Facepiece assembly: low-pressure hose, exhalation		
valve, head harness. 5. PASS device.		
PERFORMANCE RATING ON THIS SKILL: First Attempt Second Attempt	PASS	<u>FAIL</u>
Evaluator Comments:		
Evaluator #1:		
(Please Print)		
Evaluator #2:		
(Please Print)		
Notice to Evaluators: Candidate must sign for 2nd attempt	ot failures.	By this

signature the candidate is notified that he/she has failed this skill and will be required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of **this skill** plus **one additional skill** from this same area of the standard.

- Skill 11:Demonstrate donning Self-Contained Breathing Apparatus
(SCBA). NFPA 1001 2019, 4.3.1
- **CONDITION:** Wearing full protective clothing and SCBA.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

	<u>1st. Att.</u>	2nd Att.
	YN	YN
1. Check SCBA cylinder pressure gauge (verbalize pressure).		
2. Open cylinder valve fully.		
3. Check regulator and cylinder gauge verbalize pressures		
(gauges should be within 100 psi of each other).		
Don backpack and fasten/tighten all straps		
(over-the-head or coat method).		
5. Don facepiece, adjust head harness, check seal		
and exhalation valve.		
6. Don protective hood.		
7. Attach low pressure hose to regulator or face piece.		
8. Turn on or ensure PASS is active.		
9. Don helmet.		
10. Don gloves.		

* Steps may vary with different SCBA's, however all of the above should be covered during the donning process.

PERFORMANCE	E RATING ON THI	S SKILL: First Attempt Second Attempt	<u>PASS</u>	<u>FAIL</u>
Evaluator Com	nents:			
Evaluator #1:				
	(Please Print)			
Evaluator #2:	(Please Print)			

Notice to Evaluators: Candidate must sign for **2nd attempt failures**. By this signature the candidate is notified that he/she has failed this skill and will be required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of **this skill** plus **one additional skill** from this same area of the standard.

Skill 12A:	Demonstrate the following emergency procedures in the
	event of SCBA failure: Conservation of air (skip
	breathing). NFPA 1001 2019, 4.3.1

CONDITION: Wearing full protective clothing and SCBA.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

		<u>1st. Att</u>	<u>. 2nd Att.</u>
		YN	YN
1. Inhale normally (as during regular	breathing).		
2. Holds breath (as long as it would ta	ake to exhale).		
3. Inhale again.	,		
4. Exhale slowly.			
PERFORMANCE RATING ON THIS	SKILL:	<u>PASS</u>	<u>FAIL</u>
	First Attempt		
	Second Attempt		
Evaluator Comments:			
Evaluator #1:			
(Please Print)			
Evaluator #2:			
(Please Print)			
Notice to Evaluators: Candidate musignature the candidate is notified that required to take a 3rd and final attemption.	at he/she has failed thi	s skill and	will be

required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of **this skill** plus **one additional skill** from this same area of the standard.

Skill 12B:	Demonstrate the following emergency procedures in the
	event of SCBA failure: Emergency procedures in the
	event of a facepiece failure. NFPA 1001 2019, 4.3.1

CONDITION: Wearing full protective clothing, SCBA, simulated facepiece damage. 2-firefighter team

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

	<u>1st. Att.</u>	
	ΥN	ΥN
1. Notify partner of problem.		
2. Activate emergency communications (Mayday).		
3. Notify Incident command of problem.		
4. Activate PASS device.		
5. Disconnect low-pressure hose from facepiece or regulator	r. 🗆 🗖	
6. Breath from low-pressure hose or 2 nd stage regulator.		
7. Exit structure with partner.		
PERFORMANCE RATING ON THIS SKILL:	PASS	FAIL
First Attempt		
Second Attempt		
- · · · · ·		
Evaluator Comments:		
Evaluator #1:		
(Please Print)		
Evaluator #2:		
(Please Print)		
Notice to Evaluatore: Condidate must sign for 2nd attempt	failurea	Dy this

Notice to Evaluators: Candidate must sign for **2nd attempt failures**. By this signature the candidate is notified that he/she has failed this skill and will be required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of **this skill** plus **one additional skill** from this same area of the standard.

Skill 12C: Demonstrate the following emergency procedures in the event of SCBA failure: Emergency procedures in the event of an interruption/restricted air flow. NFPA 1001 2019, 4.3.1

CONDITION: Wearing full protective clothing, SCBA, simulated regulator damage and 2-firefighter team.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

		<u>1st. Att</u>	<u>. 2nd Att.</u>
 Notify partner of problem. Activate emergency communications Notify Incident command of problem Close mainline valve (if applicable). Operate By-pass: Open valve-inhale repeat as needed. Exit structure with partner. 		Y N	Y N
PERFORMANCE RATING ON THIS S	KILL: First Attempt Second Attempt	PASS	FAIL
Evaluator Comments:			
Evaluator #1:			
(Please Print)			
Evaluator #2:			
(Please Print)			
<i>Notice to Evaluators:</i> Candidate must signature the candidate is notified that	•		

required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of **this skill** plus **one additional skill** from this same area of the standard.

Skill 13A: Doff and perform a check of an in-service SCBA Without cylinder change. NFPA 1001 2019, 4.3.1

CONDITION: Given an SCBA and spare cylinder.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

* STEPS MAY VARY WITH DIFFERENT SCBA's

	<u>1st. Att</u>	<u>. 2nd Att.</u>
	Y N	YN
1. Place SCBA on ground, close cylinder valve.		
2. Relieve excess pressure from regulator, listen for		
low-pressure alarm.		
3. Check cylinder pressure (90% full),		
(verbalize pressure reading).		
4. Disconnect regulator from facepiece or low-pressure hose from regulator.		
5. Fully extend all straps on SCBA backpack		
6. Fully extend all straps on facepiece.		
7. Inspect entire apparatus for cleanliness and damage.		
PERFORMANCE RATING ON THIS SKILL:	PASS	FAIL
First Attempt		
Second Attempt		
Second Attempt Evaluator Comments:		
Evaluator Comments:		
Evaluator Comments:		
Evaluator Comments:		

signature the candidate is notified that he/she has failed this skill and will be required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of **this skill** plus **one additional skill** from this same area of the standard.

Skill 13B: Perform an SCBA cylinder change one person and two persons. NFPA 1001 2019, 4.3.1

CONDITION: Given an SCBA and spare cylinder.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

* STEPS MAY VARY WITH DIFFERENT SCBA's

- 1. Place SCBA on ground, or leave on firefighters back
- 2. Locate a full cylinder.
- 3. Close cylinder valve
- 4. Bleed off pressure
- 5. Disconnect the high pressure hose from the cylinder
- 6. Release the cylinder closing device
- 7. Replace empty cylinder with a full cylinder
- 8. Secure Full cylinder in harness
- 9. Connect high pressure hose to the cylinder
- 10. Open the cylinder and check the operation of the gauge \Box

PERFORMANCE RATING ON THIS SKILL:		PASS	FAIL
	First Attempt Second Attempt		
Evaluator Comments:			

Evaluator #1:_____

(Please Print)

Evaluator #2:

(Please Print)

Notice to Evaluators: Candidate must sign for **2nd attempt failures**. By this signature the candidate is notified that he/she has failed this skill and will be required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of **this skill** plus **one additional skill** from this same area of the standard.

Candidate's Signature:

1st. Att. 2nd Att. ΥN ΥN $\Box \Box$ $\Box\Box$ \square $\square\square$ $\square\square$ $\square\square$ \square $\square\square$ $\Box\Box$ $\square\square$ $\Box\Box$

- Skill 14: Demonstrate routine maintenance procedures for an inservice SCBA: Inspect, clean and sanitize an SCBA. NFPA 1001 2019, 4.5.1
- **CONDITION:** Given an SCBA, cleaning solution specified by manufacturer.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

		<u>1st. Att</u>	<u>2nd Att.</u>
		YN	YN
 Inspect SCBA and facepiece. Wash facepiece and sanitize 			
(verbalize sanitation procedure).			
3. Rinse in fresh water, hang to dry.			
4. Wash/rinse backpack, protecting re	egulator.		
PERFORMANCE RATING ON THIS	SKILL: First Attempt Second Attempt	PASS	FAIL
Evaluator Comments:			
Evaluator #1:			
(Please Print)			
Evaluator #2:			
(Please Print)			
Notice to Evaluators: Candidate must signature the candidate is notified that	• •		

Notice to Evaluators: Candidate must sign for **2nd attempt failures**. By this signature the candidate is notified that he/she has failed this skill and will be required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of **this skill** plus **one additional skill** from this same area of the standard.

EMERGENCY RESPONSE - APPARATUS

Skill 15: Demonstrate safety procedures for mounting, use of seat belts, hearing protection, and other safety equipment on apparatus, safely dismounting fire apparatus. NFPA 1001 2019, 4.3.2

CONDITION: Wearing full protective clothing, fire apparatus equipped with seat belts, radio headsets or other noise barriers.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

- 1. Use handrails, steps to mount apparatus.
- 2. Secures safety devices as provided.
- 3. Properly fasten seat belts.
- 4. Don hearing protection if needed.
- 5. Uses handrails and steps to dismount apparatus.

6. Deploy traffic and scene control devices as appropriate.

<u>1st. Att.</u>	2nd Att.
YN	YN

PERFORMANCE RATING ON THIS SKILL:		PASS	FAIL	
	First Attempt Second Attempt			
Evaluator Comments:				_

Evaluator #1:_____

(Please Print)

Evaluator #2:_____

(Please Print)

Notice to Evaluators: Candidate must sign for **2nd attempt failures**. By this signature the candidate is notified that he/she has failed this skill and will be required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of **this skill** plus **one additional skill** from this same area of the standard.

Skill 16:Demonstrate the proper carry and maintenance of forcible
entry tools and equipment. NFPA 1001 2019, 4.5.1

CONDITION: Wearing gloves and eye protection, given, cutting, prying, pulling, or striking tools, chainsaw, ventilation fan (PPV), soap, water, brush & rags.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

	<u>1st. Att.</u>	<u>2nd Att.</u>
	YN	YN
1. Proper carry for each tool.		
2. Protect self and others from sharp or pointed edges.		
3. Remove excess dirt with brush or hose.		
4. Wash tool with soap and water.		
5. Inspect tool head and handle for damage.		
6. Sharpen tool heads (per manufacture recommendations).7. Dry tool and protect surface per manufacture		
recommendations.		
PERFORMANCE RATING ON THIS SKILL:	PASS	FAIL
First Attempt		
Second Attempt		
Evaluator Comments:		
Evaluator #1:		
(Please Print)		
Evaluator #2:		
(Please Print)		
Notice to Evaluators: Candidate must sign for 2nd attempt		•

signature the candidate is notified that he/she has failed this skill and will be required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of **this skill** plus **one additional skill** from this same area of the standard.

Skill 17A: Demonstrate or verbalize forcible entry and through-the- lock entry techniques for a Swinging door, (stopped or rabbeted jamb). NFPA 1001 2019, 4.3.4

CONDITION: Wearing full protective clothing with eye protection (per NFPA 1500 helmet face visor is not considered appropriate eye protection), appropriate forcible entry tool.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

		<u>1st. Att</u>	<u>. 2nd Att.</u>
 Select proper entry tool(s) Proper carry of tool. Try door before prying. Correctly identify door type (stopped Pry or force entry at or near lock. Force door in correct direction. 	or rabbeted jamb).	Y N 	Y N
PERFORMANCE RATING ON THIS S	KILL: First Attempt Second Attempt	PASS	FAIL
Evaluator #1:			
(Please Print)			
Evaluator #2:			
(Please Print)			
Notice to Evaluators: Candidate must	•	•	•

Notice to Evaluators: Candidate must sign for **2nd attempt failures**. By this signature the candidate is notified that he/she has failed this skill and will be required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of **this skill** plus **one additional skill** from this same area of the standard.

Demonstrate or verbalize forcible entry and through-the- lock Skill 17B: entry techniques for a Sliding door. NFPA 1001 2019, 4.3.4

CONDITION: Wearing full protective clothing with eye protection (per NFPA 1500 helmet face visor is not considered appropriate eye protection), appropriate forcible entry tool.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

		<u>1st. Att.</u>	<u>2nd Att.</u>
		YN	YN
 Select proper entry tool(s) 			
2. Proper carry of tool.			
3. Try door before prying.			
4. Pry or force entry at or near lock.			
5. Force door away from frame.			
PERFORMANCE RATING ON THIS SH		PASS	FAIL
	First Attempt		
	Second Attempt		
Evaluator Comments:			
Evaluator #1:			
(Please Print)			
Evaluator #2:			
(Please Print)			
<i>Notice to Evaluators:</i> Candidate must signature the candidate is notified that h required to take a 3rd and final attempt,	e/she has failed this	skill and v	vill be

date. The 3rd attempt will consist of this skill plus one additional skill from this same area of the standard.

Skill 17C: Demonstrate or verbalize forcible entry and through-the-lock entry techniques for an **Overhead door.** NFPA 1001 2019, 4.3.4

CONDITION: Wearing full protective clothing with eye protection (per NFPA 1500 helmet face visor is not considered appropriate eye protection), appropriate forcible entry tool.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

		<u>1st. Att.</u>	2nd Att.
 Select proper entry tool(s) Proper carry of tool. Try door before prying. Force entry by prying upward form bottor remove door panel and open with inside lation 5. Door blocked open immediately after formation. 	atch.	Y N	Y N
	L: irst Attempt second Attempt	<u>PASS</u>	<u>FAIL</u>
Evaluator Comments:			
Evaluator #1:			
(Please Print)			
Evaluator #2:			
(Please Print)			
<i>Notice to Evaluators:</i> Candidate must signature the candidate is notified that he/ required to take a 3rd and final attempt, no date. The 3rd attempt will consist of this s same area of the standard.	she has failed th sooner than 30	nis skill and days from	will be today's

Skill 18A: Demonstrate or verbalize forcible entry and through-the-lock entry techniques for a **Sliding Windows.** NFPA 1001 2019, 4.3.4

CONDITION: Wearing full protective clothing with eye protection (per NFPA 1500 helmet face visor is not considered appropriate eye protection), appropriate forcible entry tool.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

		<u>1st. Att.</u>	<u>2nd Att.</u>
		ΥN	ΥN
 Select proper entry tool(s). 			
2. Proper carry of tool.			
3. Try window before prying.			
4. Locate lock.			
5. Pry or force entry at proper location on w	ndow.		
PERFORMANCE RATING ON THIS SKILL		PASS	FAIL
	st Attempt cond Attempt		
Evaluator Comments:			
Evaluator #1:			
(Please Print)			
Evaluator #2:			
(Please Print)			
Notice to Evaluators: Candidate must sign	for 2nd attemp	ot failures	. By this
signature the candidate is notified that he/sh	ne has failed this	s skill and	will be
required to take a 3rd and final attempt, no s	sooner than 30	days from	today's
date. The 3rd attempt will consist of this sk	i ll plus one add	itional sk	ill from this
same area of the standard.			

Skill 18B: Demonstrate or verbalize forcible entry and through-the-lock entry techniques for a **Double hung window.** NFPA 1001 2019, 4.3.4

CONDITION: Wearing full protective clothing with eye protection (per NFPA 1500 helmet face visor is not considered appropriate eye protection), appropriate forcible entry tool.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

 Select proper entry tool(s). Proper carry of tool. Try window before prying. Locate lock. Pry or force entry at proper location of 	n window.	<u>1st. Att.</u> Y N 	2nd Att. Y N
PERFORMANCE RATING ON THIS SK	GILL: First Attempt Second Attempt	PASS	FAIL
Evaluator Comments:			
Evaluator #1:			
(Please Print)			
Evaluator #2:			
(Please Print)			
<i>Notice to Evaluators:</i> Candidate must s signature the candidate is notified that he required to take a 3rd and final attempt, date. The 3rd attempt will consist of this same area of the standard.	e/she has failed this no sooner than 30 c	s skill and v lays from ⁻	will be today's

Skill 18C: Demonstrate or verbalize forcible entry and through-the-lock entry techniques for a **Casement Windows.** NFPA 1001 2019, 4.3.4

CONDITION: Wearing full protective clothing with eye protection (per NFPA 1500 helmet face visor is not considered appropriate eye protection), appropriate forcible entry tool.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

		<u>1st. Att.</u>	<u>2nd Att.</u>
 Select proper entry tool(s). Proper carry of tool. Cut screen in same area. Break lowest pane of glass. Unlock and operate window crank. Completely remove screen. 		Y N	Y N
PERFORMANCE RATING ON THIS S	KILL: First Attempt Second Attempt	PASS	FAIL
Evaluator Comments:			
Evaluator #1:			
(Please Print)			
Evaluator #2:			
(Please Print)			
Notice to Evaluators: Candidate must signature the candidate is notified that required to take a 3rd and final attempt	he/she has failed thi	s skill and	will be

signature the candidate is notified that he/she has failed this skill and will be required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of **this skill** plus **one additional skill** from this same area of the standard.

Skill 19A: Demonstrate or verbalize forcible entry for the following exterior walls: Masonry. NFPA 1001 2019, 4.3.4

CONDITION: Wearing full protective clothing with eye protection (per NFPA 1500 helmet face visor is not considered appropriate eye protection), appropriate forcible entry tool.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

	<u>1st. A</u>	<u>Att. 2nd Att.</u>
	YN	YN
1. Select proper forcible entry tool(s).		
2. Proper carry of tool.		
3. Correctly use tool(s) to force entry.		
4. Identify possible hazards associated with breach	ning wall.	
PERFORMANCE RATING ON THIS SKILL:	PASS	<u> FAIL</u>
First Atter		
Second A	ttempt	
Evaluator Comments:		
Evaluator #1:		
(Please Print)		
Evaluator #2:		
(Please Print)		
<i>Notice to Evaluators:</i> Candidate must sign for 2n signature the candidate is notified that he/she has	•	•

signature the candidate is notified that he/she has failed this skill and will be required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of **this skill** plus **one additional skill** from this same area of the standard.

Skill 19B:Demonstrate or verbalize forcible entry for the following
exterior walls: Metal. NFPA 1001 2019, 4.3.4

CONDITION: Wearing full protective clothing with eye protection (per NFPA 1500 helmet face visor is not considered appropriate eye protection), appropriate forcible entry tool.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

		<u>1st. Att.</u>	<u>2nd Att.</u>
 Select proper saw or tool. Proper carry of tool. Find and mark studs or supports. Cut along studs with saw or tool. Identify possible hazards associated with 	th breaching wall.	Y N	Y N
	LL: First Attempt Second Attempt	PASS	FAIL
Evaluator Comments:			
Evaluator #1:			
(Please Print)			
Evaluator #2:			
(Please Print)			
Notice to Evaluators: Candidate must signature the candidate is notified that he/	she has failed this	skill and v	vill be

signature the candidate is notified that he/she has failed this skill and will be required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of **this skill** plus **one additional skill** from this same area of the standard.

Skill 19C:Demonstrate or verbalize forcible entry for the following
exterior walls: Wood. NFPA 1001 2019, 4.3.4

CONDITION: Wearing full protective clothing with eye protection (per NFPA 1500 helmet face visor is not considered appropriate eye protection), appropriate forcible entry tool.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

		<u>1st. Att.</u>	2nd Att.
		YN	YN
1. Select proper tool(s).			
2. Proper carry of tool.			
3. Remove exterior covering.			
4. Sound for studs or supports.			
5. Cut along studs.			
6. Identify possible hazards associated v	with breaching wall.		
PERFORMANCE RATING ON THIS SH	(ILL:	PASS	FAIL
	First Attempt		
	Second Attempt		
Evaluator Comments:			
Evaluator #1:			
(Please Print)			
Evaluator #2:			
(Please Print)			
Notice to Evaluators: Candidate must a signature the candidate is notified that h required to take a 2rd and final attempt.	e/she has failed this	skill and v	vill be

signature the candidate is notified that he/she has failed this skill and will be required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of **this skill** plus **one additional skill** from this same area of the standard.

SAFETY

Skill 20: Establish and operate in work area at an emergency scene. NFPA 1001 2019, 4.3.3

CONDITION: Given an emergency scene, (roadway, structure fire, vehicle fire) wearing full PPE, safety vest if operating on roadway, traffic and scene control devices and an assignment.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

		<u>1st. Att.</u>	<u>2nd Att.</u>
		YN	YN
1. Don Proper PPE prior to operating or	n scene.		
2. Dismount apparatus in safe manner.			
3. Establish safety zones as directed by	IC.		
4. Operate at emergency scene within s	afety zones.		
PERFORMANCE RATING ON THIS SI	KILL:	PASS	FAIL
	First Attempt		
	Second Attempt		
Evaluator Comments:			
Evaluator #1:			
(Please Print)			
Evaluator #2:			
(Please Print)			
<i>Notice to Evaluators:</i> Candidate must signature the candidate is notified that h	• •		

signature the candidate is notified that he/she has failed this skill and will be required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of **this skill** plus **one additional skill** from this same area of the standard.

<u>SAFETY</u>

- Skill 21:Demonstrate the use of SCBA to exit through a restricted
passage. NFPA 1001 2019, 4.3.3, 4.3.9
- **CONDITION:** Wearing full protective clothing, SCBA, restricted passage where firefighter cannot pass without a low profile.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

		<u>1st. Att.</u>	<u>2nd Att.</u>
		Y N	YN
1. Loosen SCBA backpack, leave face	piece on.		
2. Move SCBA backpack to side of fire	efighter.		
3. Enter restricted passage.	0		
4. Tighten SCBA backpack after through	gh passage.		
PERFORMANCE RATING ON THIS S		PASS	<u>FAIL</u>
	First Attempt		
	Second Attempt		
Evaluator Comments:			
Evaluator #1:			
(Please Print)			
Evaluator #2:			
(Please Print)			
Notice to Evaluators: Candidate mus	t sign for 2nd attem	pt failures	. By this

Notice to Evaluators: Candidate must sign for **2nd attempt failures**. By this signature the candidate is notified that he/she has failed this skill and will be required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of **this skill** plus **one additional skill** from this same area of the standard.

<u>SAFETY</u>

Skill 22A: Demonstrate techniques for action when trapped or disoriented in a fire or hostile situation: Search for an exit using a Hose line. NFPA 1001 2019, 4.3.3, 4.3.5

CONDITION: Wearing full protective clothing, SCBA (SCBA facepiece covered), 150 ft. of 1 1/2" or larger hose with nozzle attached, appropriate size room, 2-firefighter team.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

		<u>1st. Att</u>	<u>. 2nd Att.</u>
		ΥN	ΥN
1. Call for help.			
needs for assistance 3. Activate PASS de 4. Search for and lo 5. Use hose and foll			
as guide.			
physically.	with team member(s) verbally or ea before exhausting air supply		
as a team.			
PERFORMANCE R	ATING ON THIS SKILL: First Attempt Second Attempt	PASS	FAIL
PERFORMANCE R	First Attempt Second Attempt		<u>FAIL</u>
	First Attempt Second Attempt		<u>FAIL</u>
Evaluator Commer	First Attempt Second Attempt		FAIL
Evaluator Commer	First Attempt Second Attempt		
Evaluator Commer	First Attempt Second Attempt		FAIL
Evaluator Commer	First Attempt Second Attempt		

Notice to Evaluators: Candidate must sign for **2nd attempt failures**. By this signature the candidate is notified that he/she has failed this skill and will be required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of **this skill** plus **one additional skill** from this same area of the standard.

<u>SAFETY</u>

Skill 22B:	Demonstrate techniques for action when trapped or
	disoriented in a fire or hostile situation: Search for an exit
	using wall. NFPA 1001 2019, 4.3.3, 4.3.5

CONDITION: Wearing full protective clothing, SCBA (SCBA facepiece covered), appropriate size room, 2-firefighter team.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

		<u>1st. Att. 2nd Att.</u>	
		YN	YN
1. Call for help.	r'a actional problems or		
2. Communicate to team membe needs for assistance.	s actions, problems of		
3. Activate PASS device.			
4. Search for wall.			
5. Find wall and follow to safety u	sing right or left-hand		
technique.			
6. Maintain contact with team me	mber(s) verbally or		
physically. 7. Exit hazardous area before exit	nausting air supply		
as a team.	adding an suppry		
PERFORMANCE RATING ON T	HIS SKILL:	PASS	<u>FAIL</u>
PERFORMANCE RATING ON T	First Attempt	PASS	FAIL
PERFORMANCE RATING ON T		PASS	<u>FAIL</u>
	First Attempt Second Attempt		<u>FAIL</u> □ □
PERFORMANCE RATING ON T	First Attempt Second Attempt		
	First Attempt Second Attempt		
Evaluator Comments:	First Attempt Second Attempt		
Evaluator Comments: Evaluator #1:	First Attempt Second Attempt		
Evaluator Comments: Evaluator #1: (Please Print)	First Attempt Second Attempt		
Evaluator Comments: Evaluator #1:	First Attempt Second Attempt		

Notice to Evaluators: Candidate must sign for **2nd attempt failures**. By this signature the candidate is notified that he/she has failed this skill and will be required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of **this skill** plus **one additional skill** from this same area of the standard.

Skill 23: Identify the Parts of a Ladder NFPA 1001 2019, 4.3.6

CONDITION: Given wearing full PPE, and extension ladder, the candidate shall verbally identify the parts of a ladder as detailed below.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

		<u>1st. Att. 2nd Att.</u>	
		YN	YN
1. Identify the Beam			
2. Identify the Bed Section			
3. Identify the Heel, Foot, Base, or Butt			
4. Identify the Fly Section			
5. Identify the Cleat, Shoes, or Butt Plate	es		
6. Identify the Dogs, Pawls, Rung Locks/ Ladder Locks			
7. Identify the Halyard	-		
8. Identify the Guides or Channels			
9. Identify the Sensor Label			
10. Identify the Hooks (Roof Ladder)			
11. Identify the Rungs			
12. Identify the Rails			
13. Identify the Stops			
PERFORMANCE RATING ON THIS SP	(ILL: First Attempt Second Attempt	PASS	<u>FAIL</u>
Evaluator Comments:	•		
Evaluator #1:			
(Please Print)			
Evaluator #2:			
(Please Print)			
Notice to Evaluators: Candidate must	sign for 2nd attem	ot failures	By this

Notice to Evaluators: Candidate must sign for **2nd attempt failures**. By this signature the candidate is notified that he/she has failed this skill and will be required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of **this skill** plus **one additional skill** from this same area of the standard.

Skill 24: Demonstrate the proper carry, position, raise, and lower of a roof ladder. NFPA 1001 2019, 4.3.6

CONDITION: Wearing full protective clothing, roof ladder and starting from a designated point.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

	<u>1st. Att</u>	<u>. 2nd Att.</u>
	Y N	YN
1. Start 25 ft. from structure.		
2. Lift ladder with legs to carry position.		
3. Carry ladder correctly (tip or heal forward accord	ing to	
ladder type).		
4. Check for overhead obstructions (must verbalize		
5. Determine structure stability (must verbalize).6. Butt and raise ladder to proper position.		
7. Check climbing angle.		
8. Lower ladder to ground.		
PERFORMANCE RATING ON THIS SKILL:	PASS	FAIL
First Attern	npt 🗌	
Second At	tempt	
Evaluator Comments:		
Evaluator #1:		
(Please Print)		
Evaluator #2:		
(Please Print)		
Notice to Evaluators: Candidate must sign for 2nd signature the candidate is notified that he/she has farequired to take a 3rd and final attempt, no scoper t	ailed this skill and	will be

required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of **this skill** plus **one additional skill** from this same area of the standard.

- Skill 25:Demonstrate the proper carry, position, raise, and lower of
24 ft. or 35-ft. extension ladder. NFPA 1001 2019, 4.3.6
- **CONDITION:** Wearing full protective clothing, 24-ft. extension ladder (2-firefighter team), 35-ft. extension ladder (4-firefighter team).

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

	<u>1st. Att.</u>	2nd Att.
	Y N	YN
1. Leader gives prepatory commands.		
2. Team lifts ladder with legs.		
3. Proper carry to structure.		
4. Check for overhead obstructions (must verbalize).		
5. Determine that structure is stable (must verbalize).		
6. Raise fly section to proper height.		
7. Determine locks are engaged (must verbalize).		
8. Tie off halyard.		
9. Check climbing angle.		
10. Lower ladder to ground.		
PERFORMANCE RATING ON THIS SKILL:	PASS	FAIL
First Attempt		
Second Attempt		
Evaluator Comments:		
Evaluator #1:		
(Please Print)		
Evaluator #2:		
(Please Print)		
Notice to Evaluators: Candidate must sign for 2nd attemp signature the candidate is notified that he/she has failed this	s skill and	will be

required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of **this skill** plus **one additional skill** from this same area of the standard.

- Skill 26: Demonstrate procedure for climbing, working, and descending from extension or aerial ladder with a tool, (with safety harness for aerial). NFPA 1001 2019, 4.3.6
- **CONDITION:** Wearing full protective clothing, axe, extension ladder (starting from a designated area) **OR** aerial ladder with safety harness for aerial ladder.
- SAFETY: NEVER USE LEG LOCK ON AERIAL LADDER. LADDER HEELED BY SECOND FIREFIGHTER OR TIED OFF.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

	<u>1st. Att. 2nd Att.</u>	
	YN	YN
1. Check climbing angle of ladder.		
2. Climb with arms straight, body perpendicular to		
the ground.	$\Box\Box$	
3. Climb smoothly and rhythmically.		
4. Maintain three points of contact with ladder while climbing	J	
5. Proper carry of tool.		
6. Lock-in around rung or use safety harness.		
6. Lock-in on opposite side from the working side.		
PERFORMANCE RATING ON THIS SKILL:	PASS	FAIL
First Attempt		
Second Attempt		
Evaluator Comments:		
Evaluator #1:		
(Please Print)		
Evaluator #2:		
(Please Print)		
Notice to Evaluators: Candidate must sign for 2nd attemp	t failures.	By this

signature the candidate is notified that he/she has failed this skill and will be required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of **this skill** plus **one additional skill** from this same area of the standard.

LADDERS

- **Skill 27:** Demonstrate bringing a victim down a ladder from second story window or roof. NFPA 1001 2019, 4.3.6
- **CONDITION:** Wearing full protective clothing, extension ladder, and victim: conscious or unconscious.
- SAFETY: LADDER HEELED OR TIED OFF. SAFETY LINE OR HARNESS ON VICTIM OR USE RESCUE MANIKIN.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

	<u>1st. Att</u> Y N	<u>. 2nd Att.</u> Y N
1. Ensure tip of ladder placed correctly for receive	I IN	I IN
1. Ensure tip of ladder placed correctly for rescue		
(must verbalize).		
2. Proper carry of victim (conscious or unconscious).		
PERFORMANCE RATING ON THIS SKILL:	PASS	FAIL
First Attempt	\square	
Second Attempt		
Evaluator Comments:		
Evaluator #1:		
(Please Print)		
Evaluator #2:		
(Please Print)		
Notice to Evaluators: Candidate must sign for 2nd attempt		
signature the candidate is notified that he/she has failed thi	s skill and	will be
required to take a 3rd and final attempt, no sooner than 30	days from	today's
date. The 3rd attempt will consist of this skill plus one add		

same area of the standard.

LADDERS

Skill 28: Demonstrate deployment of a roof ladder on a pitched roof. NFPA 1001 2019, 4.3.6

CONDITION: Wearing full protective clothing, roof ladder, extension ladder and 2-firefighter team. (Begin with extension ladder on building).

SAFETY: LADDER HEELED OR TIED OFF.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

	<u>1st. Att.</u> Y N	<u>2nd Att.</u> Y N
 Raise roof ladder and place against extension ladder or roof. Properly climb extension ladder. Raise roof ladder with hooks open and facing away from 		
firefighter on extension ladder. 4. Carry roof ladder to the roofline and lock-in. 5. Slide roof ladder up roof.		
6. Ensure hooks are securely grabbing peak of roof.		
PERFORMANCE RATING ON THIS SKILL: First Attempt Second Attempt Evaluator Comments:	PASS	<u>FAIL</u>
Evaluator #1:		
(Please Print)		
Evaluator #2:		
(Please Print)		
<i>Notice to Evaluators:</i> Candidate must sign for 2nd attemp		

signature the candidate is notified that he/she has failed this skill and will be required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of **this skill** plus **one additional skill** from this same area of the standard.

LADDERS

Skill 29: Demonstrate inspection, maintenance, and cleaning procedures for ground and/or aerial ladder. NFPA 1001 2019, 4.5.1

CONDITION: Given an extension ladder or a ladder on an aerial apparatus, soap, water, brush, rags and 2-firefighter team.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

	YN	<u>2nd Att.</u> Y N
 Wash ladder with water, soap, brush and then dry ladder Check rungs for looseness, cracks, dents, or 		
unusual wear.		
 Check all bolts, rivets, and welds for looseness. Check beams, trusses, and truss blocks for damage. 		
5. Check all braces, slides, stops, and locks.		
 6. Check pulleys and halyards. 7. Check heat sensor labels for color change. 		
8. Mark any defects found.		
9. Check for smooth operation by raising and lowering ladder.		
PERFORMANCE RATING ON THIS SKILL: First Attempt Second Attempt	<u>PASS</u> 	<u>FAIL</u>
First Attempt		
First Attempt Second Attempt		
First Attempt Second Attempt		
First Attempt Second Attempt		
First Attempt Second Attempt		
First Attempt Second Attempt Evaluator Comments: Evaluator #1:		
First Attempt Second Attempt Evaluator Comments: Evaluator #1: (Please Print)		

signature the candidate is notified that he/she has failed this skill and will be required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of **this skill** plus **one additional skill** from this same area of the standard.

- Skill 30: Demonstrate proper set-up a Master stream, (300 gpm or greater). NFPA 1001 2019, 4.3.8
- **CONDITION:** Wearing full protective clothing, water supply, master stream appliance, 100 ft. 2 1/2" hose or larger, 2-firefighter team.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

	<u>1st. Att</u>	<u>. 2nd Att.</u>
 Set up appliance. Connect hoseline from apparatus to appliance. Signal for water. Exercise safety as hose lines charge. Adjust stream of appliance once water is at nozzle. Flow water. 	Y N	Y N
PERFORMANCE RATING ON THIS SKILL: First Attempt Second Attempt	PASS	FAIL
Evaluator Comments:		
Evaluator #1:		
(Please Print)		
Evaluator #2:		
(Please Print)		
<i>Notice to Evaluators:</i> Candidate must sign for 2nd attem signature the candidate is notified that he/she has failed th required to take a 3rd and final attempt, no sooner than 30 date. The 3rd attempt will consist of this skill plus one ad	nis skill and) days from	will be today's

same area of the standard.

- Skill 31:Demonstrate the proper method for extending
hose line. NFPA 1001 2019, 4.3.10
- **CONDITION:** Wearing full protective clothing, 150 ft. of 1 1/2" or larger hose, hose clamp, nozzle, 2-firefighter team

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

		<u>1st. Att.</u> Y N	<u>2nd Att.</u> Y N
 Clamp hose approximately 3 ft. behin remove nozzle. Add 50-ft. section of hose. Replace nozzle and charge hoseline section of hose. 			
PERFORMANCE RATING ON THIS SP	(ILL: First Attempt Second Attempt	PASS	FAIL
Evaluator Comments:			
Evaluator #1:			
(Please Print) Evaluator #2:			
(Please Print)			
<i>Notice to Evaluators:</i> Candidate must signature the candidate is notified that h	• •		•

signature the candidate is notified that he/she has failed this skill and will be required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of **this skill** plus **one additional skill** from this same area of the standard.

- Skill 32: Demonstrate the proper method for <u>replacing</u> a burst section of hose. NFPA 1001 2019, 4.3.10
- **CONDITION:** Wearing full protective clothing, 150-ft. of 1 1/2" or larger hose, hose clamp, nozzle, and 2-firefighter team.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

		<u>1st. Att.</u>	<u>2nd Att.</u>
 Clamp hose approximately 3 ft. behin Drain hose at nozzle. Replace 2 sections for one burst sec Remove hose clamp and charge hose 	tion.	Y N 	Y N
PERFORMANCE RATING ON THIS S	KILL: First Attempt Second Attempt	PASS	<u>FAIL</u>
Evaluator Comments:			
Evaluator #1:			
(Please Print)			
Evaluator #2:			
(Please Print)			
Notice to Evaluators: Candidate must	sign for 2nd attempt	ot failures.	By this

Notice to Evaluators: Candidate must sign for **2nd attempt failures**. By this signature the candidate is notified that he/she has failed this skill and will be required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of **this skill** plus **one additional skill** from this same area of the standard.

Skill 33A: Demonstrate coupling and uncoupling hose using the: Foottilt method. NFPA 1001 2019, 4.3.10

CONDITION: Wearing gloves, 100 ft. of 1 1/2" or larger hose.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

			2nd Att.
1 Diago fact habing male and of horse on	d apply pressure	ΥN	ΥN
1. Place foot behind male end of hose an	d apply pressure		
to tilt male coupling.			
2. Connect female end to male end.			
PERFORMANCE RATING ON THIS SKI	LL:	PASS	FAIL
	First Attempt		
	Second Attempt		
Evaluator Comments:			
Evaluator #1:			
(Please Print)			
Evaluator #2:			
(Please Print)			
<i>Notice to Evaluators:</i> Candidate must s signature the candidate is notified that he	she has failed this	skill and	will be
required to take a 3rd and final attempt, r	io sooner than 30 c	lavs from	todav's

date. The 3rd attempt will consist of **this skill** plus **one additional skill** from this same area of the standard.

Skill 33B: Demonstrate coupling and uncoupling hose using the: Two-Firefighter method. NFPA 1001 2019, 4.3.10

CONDITION: Wearing gloves, 100 ft. of 1 1/2" or larger hose.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

		<u>1st. Att. 2nd Att.</u>	
		YN	YN
 One firefighter holds male coupling and one firefighter holds female coupling. Firefighter holding female coupling connects hose to 			
male coupling using the Higbee indic	ator as a guide.		
PERFORMANCE RATING ON THIS	-	PASS	FAIL
	First Attempt Second Attempt		
Evaluator Comments:			
Evaluator #1:			
(Please Print)			
Evaluator #2:			
(Please Print)			
Notice to Evaluators: Candidate musignature the candidate is notified that required to take a 3rd and final attempt date. The 3rd attempt will consist of the second sec	at he/she has failed thi opt, no sooner than 30	s skill and days from	will be today's

Candidate's Signature:

same area of the standard.

Skill 34A: Demonstrate the proper method for advancing a charged or uncharged attack line from a pumper: for a ground level fire attack (structural, ground cover, vehicle). NFPA 1001 2019, 4.3.10

CONDITION: Wearing full protective clothing, SCBA, 150-ft. of 1 1/2" or larger hose, nozzle.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

		<u>1st. Att</u>	<u>. 2nd Att.</u>
		YN	YN
1. Correctly unload hose from apparatu	S.		
2. Advance hose to attack position.			
3. Signal for water.			
4. Open nozzle to bleed air from the att	ack line and		
check stream pattern.			
PERFORMANCE RATING ON THIS S	KILL:	PASS	FAIL
	First Attempt		
	Second Attempt		
Evaluator Comments:			
Evaluator #1:			
(Please Print)			
Evaluator #2:			
(Please Print)			
<i>Notice to Evaluators:</i> Candidate must signature the candidate is notified that required to take a 3rd and final attempt date. The 3rd attempt will consist of thi	ne/she has failed thi , no sooner than 30	s skill and days from	will be today's
same area of the standard.			

Skill 34B:Demonstrate the proper method for advancing a charged or
uncharged line from a pumper to an: Up a ladder to a
Second floor window or roof. NFPA 1001 2019, 4.3.10

CONDITION: Wearing full protective clothing, SCBA, 2-firefighter team, 150-ft. of 1 1/2" or larger hose, nozzle, extension ladder, hose straps or webbing.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

		<u>1st. Att. 2nd Att</u>	
		ΥN	YN
1. Correctly unload hose from appara	atus.		
2. Advance hose up the ladder.			
3. Secure hose to ladder with hose s	traps or webbing.		
4. Signal for water.			
5. Open nozzle to bleed air from atta	ck line and check		
stream pattern.			
PERFORMANCE RATING ON THIS	SKILL:	PASS	FAIL
	First Attempt		
	Second Attempt		
Evaluator Comments:			
Evaluator #1:			
(Please Print)			
Evaluator #2:			
(Please Print)			
Notice to Evaluators: Candidate mu	ust sign for 2nd attem	pt failures	. By this

Notice to Evaluators: Candidate must sign for **2nd attempt failures**. By this signature the candidate is notified that he/she has failed this skill and will be required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of **this skill** plus **one additional skill** from this same area of the standard.

Skill 34C: Demonstrate the proper method for advancing a charged or uncharged line from a pumper: Up OR down an Inside OR outside stairway to an upper OR lower floor. NFPA 1001 2019, 4.3.10

CONDITION: Wearing full protective clothing, SCBA, 2-firefighter team, 150-ft. of 1 1/2" or larger hose, nozzle.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

		<u>1st. Att</u>	<u>. 2nd Att.</u>
 Correctly unload hose from apparate Advance to door, feel door for heat Signal for water. 		Y N 	Y N
4. Open nozzle to bleed air from line a stream pattern.5. Advance up OR down 2 flights of st6. Lay hose against outside wall.			
PERFORMANCE RATING ON THIS	SKILL: First Attempt Second Attempt	PASS	FAIL
Evaluator Comments:			
Evaluator #1:			
(Please Print)			
Evaluator #2:			
(Please Print)			
Notice to Evaluators: Candidate must signature the candidate is notified that required to take a 3rd and final attemption.	t he/she has failed thi	s skill and	will be

required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of **this skill** plus **one additional skill** from this same area of the standard.

Skill 35:	Demonstrate how to connect to a standpipe and advance a
	hose line from the standpipe. NFPA 1001 2019, 4.3.10

CONDITION: Wearing full protective clothing, 100-ft. of 1 1/2" or larger hose, nozzle, 2-firefighter team.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

 Advance to standpipe with needed of Connect to standpipe at connection Properly position hose line in stairw Advance the entire hose length, avoid Signal for water. Open nozzle to bleed air from attack stream pattern. 	below fire floor. ell. biding kinks.	<u>1st. Att.</u> Y N	2nd Att. Y N
PERFORMANCE RATING ON THIS	SKILL:	PASS	FAIL
	First Attempt		
	Second Attempt		
Evaluator Comments:			
Evaluator #1:			
(Please Print)			
Evaluator #2:			
(Please Print)			
<i>Notice to Evaluators:</i> Candidate must signature the candidate is notified that required to take a 3rd and final attempt date. The 3rd attempt will consist of th same area of the standard.	he/she has failed this t, no sooner than 30 (s skill and [.] days from	will be today's

Skill 36A:	Demonstrate the following hose carry: Single section drain
	and carry. NFPA 1001 2019, 4.3.10

CONDITION: Wearing full protective clothing, 50-ft. of 1 1/2" or larger hose.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

		<u>1st. Att.</u>	<u>2nd Att.</u>
 Pick-up coupling allowing water to drain. Place coupling in front of body with hose loop over shoulder. 		Y N	Y N □□
3. Layer hose on shoulder.			
4. Hose controlled and secured.			
PERFORMANCE RATING ON THIS S	KILL: First Attempt Second Attempt	PASS	<u>FAIL</u>
Evaluator Comments:			
Evaluator #1:			
(Please Print)			
Evaluator #2:			
(Please Print)			
Notice to Evaluators: Candidate must signature the candidate is notified that required to take a 3rd and final attempt	he/she has failed thi	s skill and	will be

signature the candidate is notified that he/she has failed this skill and will be required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of **this skill** plus **one additional skill** from this same area of the standard.

Skill 36B:	Demonstrate the following hose carry: Accordion shoulder
	carry. NFPA 1001 2019, 4.3.10

CONDITION: Wearing full protective clothing, 50-ft. of 1 1/2" or larger hose.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

		<u>1st. Att.</u>	<u>2nd Att.</u>
 Fold hose on ground. Line up folds and couplings. Lift hose to shoulder using legs. 		YN	Y N
4. Hose controlled and secured.			
PERFORMANCE RATING ON THIS	SKILL: First Attempt Second Attempt	PASS	FAIL
Evaluator Comments:			
Evaluator #1:			
(Please Print)			
Evaluator #2:			
(Please Print)			
Notice to Evaluators: Candidate must	st sign for 2nd attem	pt failures	. By this

Notice to Evaluators: Candidate must sign for **2nd attempt failures**. By this signature the candidate is notified that he/she has failed this skill and will be required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of **this skill** plus **one additional skill** from this same area of the standard.

Skill 37A:	Demonstrate the following hose loads: flat or accordion.
	NFPA 1001 2019, 4.5.2

CONDITION:	With gloves,	150-ft.	of 2 1/	/2" or la	arger hose,	3-firefighter
	team					

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

		<u>1st. Att</u>	<u>2nd Att.</u>
		ΥN	ΥN
1. Layer hose in hose bed.			
2. Use "Dutchman" where appropriate.			
PERFORMANCE RATING ON THIS S	KILL:	PASS	<u>FAIL</u>
	First Attempt		
	Second Attempt		
Evaluator Comments:			
Evaluator #1:			
(Please Print)			
Evaluator #2:			
(Please Print)			
Notice to Evaluators: Candidate must	sign for 2nd attemp	t failures	By this
signature the candidate is notified that I	• •		
required to take a 3rd and final attempt			
date. The 3rd attempt will consist of thi		•	•
uale. The ord allempt will consist of the	a aniii pius uiie auu	iliviiai Sk	

Candidate's Signature:_____

same area of the standard.

- Skill 37B:Demonstrate the following hose loads: attach hose using
Flat or Triple Layer or Minuteman hose loads.
NFPA 1001 2019, 4.5.2
- **CONDITION:** With gloves, 150-ft. of 1 1/2" or larger hose, 3-firefighter team

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

		<u>1st. Att.</u>	<u>2nd Att.</u>
		YN	YN
1. Attach female coupling to discharge.			
2. Layer hose in hose bed.			
3. Use "Dutchman" where appropriate.			
4. Finishes load with nozzle in correct load	cation and secured.		
PERFORMANCE RATING ON THIS SK		<u>PASS</u>	<u>FAIL</u>
	First Attempt		
	Second Attempt		
Evaluator Comments:			
Evaluator #1:			
(Please Print)			
Evaluator #2:			
(Please Print)			
Notice to Evaluators: Candidate must signature the candidate is notified that he			

signature the candidate is notified that he/she has failed this skill and will be required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of **this skill** plus **one additional skill** from this same area of the standard.

Demonstrate the following hose roll: Straight roll. Skill 38A: NFPA 1001 2019, 4.5.2

With gloves, 50 ft. of 1 1/2" or larger. CONDITION:

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

			2nd Att.
 Roll hose with male coupling in the center. Lay completed roll on ground, tamp protruding coils. 		Y N 	Y N
PERFORMANCE RATING ON THIS	SKILL: First Attempt Second Attempt	PASS	FAIL
Evaluator Comments:			
Evaluator #1:			
(Please Print) Evaluator #2:			
(Please Print)			
Notice to Evaluators: Candidate musignature the candidate is notified that required to take a 3rd and final attem	at he/she has failed thi	s skill and	will be

date. The 3rd attempt will consist of this skill plus one additional skill from this same area of the standard.

Candidate's Signature:

Skill 38B: Demonstrate the following hose roll: Donut roll. NFPA 1001 2019, 4.5.2

CONDITION: With gloves, 50 ft. of 1 1/2" hose or larger.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

	<u>1st. Att</u> Y N	<u>. 2nd Att.</u> Y N
1. Poll base with male coupling inside roll and female	I IN	I IN
1. Roll hose with male coupling inside roll and female		
coupling approximately 3' ahead of male coupling.		
2. Lay completed roll on ground, tamp protruding coils.		
PERFORMANCE RATING ON THIS SKILL:	PASS	FAIL
First Attempt		
Second Attemp	ot 🗍	
Evaluator Comments:		
Evaluator #1:		
(Please Print)		
Evaluator #2:		
(Please Print)		
Notice to Evaluators: Candidate must sign for 2nd atte signature the candidate is notified that he/she has failed required to take a 3rd and final attempt, no sooner than date. The 3rd attempt will consist of this skill plus one a	this skill and 30 days from	will be today's

Candidate's Signature:

same area of the standard.

- Skill 39: Demonstrate the procedures for cleaning, inspecting and maintaining: Fire hose and couplings. NFPA 1001 2019, 4.5.2
- **CONDITION:** Fire hose, soap, water, brush or hose washing and drying equipment.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

		<u>1st. Att.</u>	2nd Att.
		ΥN	ΥN
 Wash hose using clear water and a luse mild soap. Rinse with clear water. Wash coupling with clear water and Inspect hose for mechanical, thermal Inspect couplings for damage. Remove gasket from female coupling. Reinstall gasket in female coupling. Check male threads for damage by the female coupling. Mark and record any damage found from service. 	a brush. I, chemical damage. g, check for cracks. hreading into		□□ □□ □□ □□ □□ remove
PERFORMANCE RATING ON THIS S Evaluator Comments:	KILL: First Attempt Second Attempt	PASS	FAIL
Evaluator #1:			
(Please Print)			
Evaluator #2:			
(Please Print)			
Notice to Evaluators: Candidate must	sign for 2nd attemn	t failuros	By this

Notice to Evaluators: Candidate must sign for **2nd attempt failures**. By this signature the candidate is notified that he/she has failed this skill and will be required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of **this skill** plus **one additional skill** from this same area of the standard.

- **Skill 40:** Demonstrate proper techniques while conducting a search for a victim in a structure (with or without hose line or safety rope) and remove victim to safe area. NFPA 1001 2019, 4.3.9
- **CONDITION:** Wearing full protective clothing, SCBA (covered facepiece), forcible entry tool, 2-firefighter team, and appropriate size room.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

	<u>1st. Att</u>	<u>. 2nd Att.</u>
 Search on hands and knees. Use right or left hand search pattern. Call out for victim. Pause occasionally to listen for sounds. Locate victim and communicate it to command. Remove victim to safe area using appropriate drag 	Y N	Y N
or carry. 7. Team integrity is maintained during search.		
PERFORMANCE RATING ON THIS SKILL: First Attempt Second Attempt Evaluator Comments:	PASS	<u>FAIL</u>
Evaluator #1:		
(Please Print)		
Evaluator #2:		
(Please Print)		
Notice to Evaluators: Candidate must sign for 2nd attemp		•

Notice to Evaluators: Candidate must sign for **2nd attempt failures**. By this signature the candidate is notified that he/she has failed this skill and will be required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of **this skill** plus **one additional skill** from this same area of the standard.

- Skill 41A: Demonstrate proper rescue procedures for moving a civilian victim 40-ft. using the **extremities carry**. NFPA 1001 2019, 4.3.9
- **CONDITION:** Wearing full protective clothing, 2-firefighter team, and civilian victim.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

		<u>1st. Att.</u>	<u>2nd Att.</u>
		Y N	YN
1. Firefighter at head gives commands.			
2. Lift with legs.			
3. Perform correct carry.			
4. Move victim 40 feet.			
PERFORMANCE RATING ON THIS SI	KILL:	PASS	FAIL
	First Attempt		
	Second Attempt		
Evaluator Comments:			
Evaluator #1:			
(Please Print)			
Evaluator #2:			
(Please Print)			
Notice to Evaluators: Candidate must signature the candidate is notified that h required to take a 3rd and final attempt	ne/she has failed tl	nis skill and	will be

required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of **this skill** plus **one additional skill** from this same area of the standard.

- Skill 41B: Demonstrate proper rescue procedures for moving an unconscious firefighter with or without functioning SCBA, 40-feet using the: coat drag. NFPA 1001 2019, 4.3.9
- **CONDITION:** Wearing full protective clothing, 2-firefighter team, firefighter victim.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

		<u>1st. Att.</u>	2nd Att.
		ΥN	YN
1. Place firefighter face-up.			
2. Grasp fire coat by collar.			
3. Work as a team to move firefighter to	safe area.		
4. Move victim 40 feet.			
PERFORMANCE RATING ON THIS SK		PASS	FAIL
	First Attempt		
	Second Attempt		
Evaluator Comments:			
Evaluator #1:			
(Please Print)			
Evaluator #2:			
(Please Print)			
<i>Notice to Evaluators:</i> Candidate must signature the candidate is notified that h	e/she has failed thi	s skill and	will be
required to take a 3rd and final attempt	no sooner than 30	nave trom	IndaV.e

required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of **this skill** plus **one additional skill** from this same area of the standard.

Skill 41C: Demonstrate proper rescue procedures for moving an unconscious victim 40-feet using the: blanket drag. NFPA 1001 2019, 4.3.9

CONDITION: Wearing full protective clothing, 2-firefighter team, firefighter victim and a blanket.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

		<u>1st. Att.</u>	<u>2nd Att.</u>
1. Place victim face-up.		Y N	Y N
 Roll victim to one side and place blan Roll victim opposite side and pull blan side of victim. 			
4. Work as a team, grasp blanket near v	victim's head and		
move to safe area. 5. Move victim 40 feet.			
PERFORMANCE RATING ON THIS SI	(ILL: First Attempt Second Attempt	PASS	FAIL
Evaluator Comments:			
Evaluator #1:			
(Please Print) Evaluator #2:			
(Please Print)			
<i>Notice to Evaluators:</i> Candidate must signature the candidate is notified that h			

signature the candidate is notified that he/she has failed this skill and will be required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of **this skill** plus **one additional skill** from this same area of the standard.

Skill 42: Determine the integrity of a roof by sounding. NFPA 1001 2019, 4.3.12

CONDITION: Wearing full protective clothing, axe, ladder, rope.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

		<u>1st. Att.</u>	2nd Att.
		ΥN	ΥN
1. Sound roof before stepping on.			
2. Stay on roof supports.			
3. Sound roof to locate supports.			
4. Mark location of rafters or solid supp	ports.		
PERFORMANCE RATING ON THIS S	SKILL:	PASS	FAIL
	First Attempt		
	Second Attempt		
Evaluator Comments:			
Evaluator #1:			
(Please Print)			
Evaluator #2:			
(Please Print)			
Notice to Evaluators: Candidate mus	t sign for 2nd attem	pt failures	. By this

signature the candidate is notified that he/she has failed this skill and will be required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of **this skill** plus **one additional skill** from this same area of the standard.

Skill 43A: Demonstrate procedures for breaking window or door glass and removing obstructions while working from: Ground Level. NFPA 1001 2019, 4.3.11

CONDITION: Wearing full protective clothing, pike pole or axe.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

		<u>1st. Att.</u>	<u>. 2nd Att.</u>
 Stand to windward side of glass pane Strike with tool at top of pane. Keep hands above point of impact. Stand at 45-degree angle of window/or stand at 45-degree angle of		Y N	Y N
pike pole.5. Clear all glass from frame or track.6. Remove screens and drapes.			
PERFORMANCE RATING ON THIS SP	KILL: First Attempt Second Attempt	PASS	FAIL
Evaluator Comments:			
Evaluator #1:			
(Please Print)			
Evaluator #2:			
(Please Print)			
<i>Notice to Evaluators:</i> Candidate must signature the candidate is notified that h			

signature the candidate is notified that he/she has failed this skill and will be required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of **this skill** plus **one additional skill** from this same area of the standard.

Skill 43B: Demonstrate procedures for breaking window or door glass and removing obstructions while working from: Ladder. NFPA 1001 2019, 4.3.11

CONDITION: Wearing full protective clothing, pike pole or axe, ladder.

SAFETY: LADDER HEELED OR TIED OFF ON STUCTURE.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

 Place ladder to windward side of win Correctly lock-in on ladder. Strike with tool at top of pane. Keep hands above point of impact. Clear all glass from frame or track. Remove screens and drapes. 	idow.	<u>1st. Att.</u> Y N 	2nd Att. Y N
PERFORMANCE RATING ON THIS S	KILL: First Attempt Second Attempt	PASS	<u>FAIL</u> □ □
Evaluator #1:			
(Please Print)			
Evaluator #2:			
(Please Print)			
Notice to Evaluators: Candidate must		-	•

signature the candidate is notified that he/she has failed this skill and will be required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of **this skill** plus **one additional skill** from this same area of the standard.

- Skill 44A: Demonstrate opening a 4'X4' ventilation hole for all of the following for vertical ventilation: Pitched or Flat roof. NFPA 1001 2019, 4.3.12
- **CONDITION:** Wearing full protective clothing, fire axe, power saw, pike pole, roof ladder, and 3-firefighter team.

SAFETY: LADDER HEELED OR TIED OFF ON STUCTURE.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

- 1. Proper placement of roof ladder, windward side.
- 2. Use spotter for safety.
- 3. Sound roof and mark rafters or structural supports.
- 4. Remove built up roof material.
- 5. Correctly open ventilation hole.
- 6. Use pike pole to remove any barriers.
- 7. Exit roof area once ventilation hole is completed.

PERFORMANCE RATING O	N THIS SKILL: First Attempt Second Attempt	PASS	<u>FAIL</u>
Evaluator Comments:			
Evaluator #1:			
(Please Print)		
Evaluator #2:			
(Please Print)		
Notice to Evaluators: Candi	date must sign for 2nd attem	ot failures	. Bv this

signature the candidate is notified that he/she has failed this skill and will be required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of **this skill** plus **one additional skill** from this same area of the standard.

Candidate's Signature:

1st. Att. 2nd Att.

ΥN

 $\square\square$

 $\square\square$

 \square

 $\square\square$

YN


 \square

 \square

- Skill 44B: Demonstrate opening a 4'X4' ventilation hole for all of the following for vertical ventilation: Floor. NFPA 1001 2019, 4.3.12
- CONDITION: Wearing full protective clothing, chain or circular saw, or axe, pike pole, 2-firefighter team.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

- 1. Sound floor for structural supports
- 2. Correctly open ventilation hole.
- 3. Use pike pole to remove any barriers.
- 4. Exit once ventilation hole is completed.



PERFORMANCE RATING ON THIS SKILL:		PASS	FAIL	
	First Attempt Second Attempt			
Evaluator Comments:				

Evaluator	Comments:
-----------	-----------

Evaluator #1:		
	(Please Print)	
Evaluator #2:		

(Please Print)

Notice to Evaluators: Candidate must sign for **2nd attempt failures**. By this signature the candidate is notified that he/she has failed this skill and will be required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of this skill plus one additional skill from this same area of the standard.

Skill 45: Demonstrate the proper set up of a smoke ejector in a door or window to ventilate a structure using "**negative**" pressure ventilation. NFPA 1001 2019, 4.3.11

CONDITION: Wearing full protective clothing, SCBA, 2-firefighter team, smoke ejector.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

	<u>1st. Att</u>	<u>. 2nd Att.</u>
	ΥN	YN
 Place smoke ejector to exhaust in the same direction as the natural wind. Seal around ejector to eliminate air churning. Open windows and doors on windward side of structure 		
 to aid in ventilation process. 4. Keep airflow in as straight a line as possible. 5. Remove all obstacles to airflow. 6. Starts smoke ejector. 		
PERFORMANCE RATING ON THIS SKILL:	PASS	FAIL
First Attempt Second Attempt		
Evaluator Comments:		
Evaluator #1:		
(Please Print)		
Evaluator #2:		
(Please Print)		
Notice to Evaluators: Candidate must sign for 2nd attemp		

signature the candidate is notified that he/she has failed this skill and will be required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of **this skill** plus **one additional skill** from this same area of the standard.

Skill 46: Demonstrate the proper set up of a high volume blower fan in a doorway to ventilate a structure using "**Positive**" pressure ventilation. NFPA 1001 2019, 4.3.11

CONDITION: Wearing full protective clothing, SCBA 2-firefighter team, and positive-pressure ventilation blower/fan.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

	<u>1st. Att. 2nd Att.</u>	
	ΥN	ΥN
 Start positive pressure blower. Set blower so that the cone of air from the blower 		
 completely covers the door opening. 3. Set blower so placement does not interfere with entry and exit of firefighters from the building. 4. Exhaust opening should be 75 to 150 percent as large as the entry opening. 5. Open interior doors systematically to maintain positive 		
pressure in the structure.		
PERFORMANCE RATING ON THIS SKILL:	PASS	FAIL
First Attempt Second Attempt		
Evaluator Comments:		
Evaluator #1:		
(Please Print)		
Evaluator #2:		
(Please Print)		
Notice to Evaluators: Candidate must sign for 2nd attemp		

signature the candidate is notified that he/she has failed this skill and will be required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of **this skill** plus **one additional skill** from this same area of the standard.

OVERHAUL OPERATIONS

- **Skill 47:** Demonstrate search and exposure of hidden fires in: walls, ceilings, and floors. NFPA 1001 2019, 4.3.13
- **CONDITION:** Wearing full protective clothing, appropriate tools, flashlight, hoseline, or water extinguisher.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

	<u>1st. Att. 2nd Att.</u>	
	ΥN	ΥN
1. Search for hidden fires using: sight, touch, sound, or		
electronic sensors.		
2. Feel for heat with the back of ungloved hand.		
3. With appropriate tool open walls, ceilings, floors to		
expose hidden fire.	$\Box \Box$	
4. Expose void spaces without compromising structural		
integrity.		
5. Use water as needed to extinguish hidden fires as found.		
6. Fire cause evidence is preserved.		
PERFORMANCE RATING ON THIS SKILL:	PASS	<u>FAIL</u>
First Attempt		
Second Attempt		
Evaluator Comments:		
Evaluator #1:		
(Please Print)		
Evaluator #2:		
(Please Print)		
Notice to Evaluators: Candidate must sign for 2nd attemp signature the candidate is notified that he/she has failed this	skill and	will be

required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of **this skill** plus **one additional skill** from this same area of the standard.

Skill 48A: Demonstrate the proper folds and rolls for salvage covers: for a **One-firefighter** spread. NFPA 1001 2019, 4.3.14

CONDITION: Wearing full protective clothing, AHJ approved salvage cover, 2-firefighter team.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

		<u>1st. Att.</u>	<u>2nd Att.</u>
		YN	YN
1. Fold cover to reduce size.			
2. Fold with finish side out.			
3. Finish cover by rolling or folding.			
PERFORMANCE RATING ON THIS SK	ILL:	PASS	FAIL
	First Attempt		
	Second Attempt		
Evaluator Comments:			
Evaluator #1:			
(Please Print)			
Evaluator #2:			
(Please Print)			
Notice to Evaluators: Candidate must s signature the candidate is notified that he	e/she has failed this	skill and v	will be

Notice to Evaluators: Candidate must sign for **2nd attempt failures**. By this signature the candidate is notified that he/she has failed this skill and will be required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of **this skill** plus **one additional skill** from this same area of the standard.

Skill 48B:	Demonstrate the proper folds and rolls for salvage covers:
	for a Two-firefighter spread. NFPA 1001 2019, 4.3.14

CONDITION: Wearing full protective clothing, AHJ approved salvage cover, 2-firefighter team.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

		<u>1st. Att</u>	<u>. 2nd Att.</u>		
		ΥN	YN		
1. Fold cover to reduce size.					
2. Fold with finish side out.					
3. Finish cover by folding for two-	firefighter spread.				
PERFORMANCE RATING ON T	HIS SKILL:	PASS	FAIL		
	First Attempt				
	Second Attempt				
Evaluator Comments:					
Evaluator #1:					
(Please Print)					
Evaluator #2:					
(Please Print)					
Notice to Evaluators: Candidate signature the candidate is notified	I that he/she has failed thi	s skill and	will be		

signature the candidate is notified that he/she has failed this skill and will be required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of **this skill** plus **one additional skill** from this same area of the standard.

- Skill 49A: Demonstrate the proper deployment of a salvage cover using a **One-firefighter** deployment. NFPA 1001 2019, 4.3.14
- **CONDITION:** Wearing full protective clothing, AHJ approved salvage cover.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

		<u>1st. Att.</u>	<u>2nd Att.</u>
1. Stack or cluster objects to be covered		Y N	YN □□
2. Lay cover in the center of objects to b	e covered.		
 Unfold or unroll cover over all objects. Snap cover open at ends. 			
5. Tuck cover in at bottom.			
PERFORMANCE RATING ON THIS SK	ILL: First Attempt Second Attempt	PASS	FAIL
Evaluator Comments:			
Evaluator #1:			
(Please Print)			
Evaluator #2:			
(Please Print)			
<i>Notice to Evaluators:</i> Candidate must s signature the candidate is notified that he required to take a 3rd and final attempt,	e/she has failed this	skill and v	will be

required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of **this skill** plus **one additional skill** from this same area of the standard.

Skill 49B: Demonstrate the proper deployment of a salvage cover using a **Two-firefighter** (Balloon Throw) deployment. NFPA 1001 2019, 4.3.14

CONDITION: Wearing full protective clothing, 2-firefighter team, AHJ approved salvage cover.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

		<u>1st. Att.</u>	<u>2nd Att.</u>
		YN	YN
1. Stack or cluster objects to be covere			
2. Stretch cover along one side of the c			
3. Make several accordion folds with in			
4. Pull the cover tight and throw, pocke	t as much air		
as possible.	la at ta ba aay anad		
5. As a team float the cover over the ob	-		
6. Guide into position and tuck in at bot	lom.		
PERFORMANCE RATING ON THIS S		PASS	FAIL
	First Attempt		
	Second Attempt		H
	eeeena / monipt		
Evaluator Comments:			
Evaluator #1:			
(Please Print)			
Evaluator #2:			
(Please Print)			
Notice to Evaluators: Candidate must sign for 2nd attempt failures . By this signature the candidate is notified that he/she has failed this skill and will be required to take a 2rd and final attempt, no account than 20 days from today's			

signature the candidate is notified that he/she has failed this skill and will be required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of **this skill** plus **one additional skill** from this same area of the standard.

- Skill 50: Demonstrate the proper construction of a water chute (minimum 10ft.) down a stairwell or out a window. NFPA 1001 2019, 4.3.14
- **CONDITION:** Wearing full protective clothing, 2-firefighter team, salvage cover, attic ladder or 2 pike poles.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

		<u>1st. Att. 2nd Att.</u>		
 Open salvage cover. Roll salvage cover edges over pike poles and turn over to create water chute. Adjust water chute on ladder for water removal out. 		Y N	Y N	
window. 4. Remove water from structure.				
4. Remove water from structure.				
PERFORMANCE RATING ON THIS S	KILL: First Attempt Second Attempt	PASS	<u>FAIL</u> □ □	
Evaluator Comments:				
Evaluator #1:				
(Please Print)				
Evaluator #2:				
(Please Print)				
Notice to Evaluators: Candidate must sign for 2nd attempt failures . By this signature the candidate is notified that he/she has failed this skill and will be required to take a 3rd and final attempt, no scoper than 30 days from today's				

required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of **this skill** plus **one additional skill** from this same area of the standard.

- Skill 51:Demonstrate the proper construction of a catchall.NFPA 1001 2019, 4.3.14
- **CONDITION:** Wearing full protective clothing, 2-firefighter team, AHJ approved salvage cover.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

		<u>1st. Att.</u>	<u>2nd Att.</u>
		YN	YN
1. Open salvage cover.			
2. Fold corners inward at 45 degree.			
3. Roll side inward approximately 3 ft.			
4. Tuck the end roll under the side roll to	lock.		
PERFORMANCE RATING ON THIS SK	(ILL:	PASS	FAIL
	First Attempt		
	Second Attempt		
Evaluator Comments:			
Evaluator #1:			
(Please Print)			
Evaluator #2:			
(Please Print)			
<i>Notice to Evaluators:</i> Candidate must signature the candidate is notified that he			

signature the candidate is notified that he/she has failed this skill and will be required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of **this skill** plus **one additional skill** from this same area of the standard.

Skill 52: Demonstrate the covering or closing of building openings including: doors, windows, floors, and roofs. NFPA 1001 2019, 4.3.14

CONDITION: Wearing full protective clothing, 2-firefighter team, and appropriate materials to cover openings.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

 Select correct material to cover ope Use sufficient amount of material to opening completely. Tack edges of material down comp weather out. 	cover	<u>1st. Att.</u> Y N □□	2nd Att. Y N
PERFORMANCE RATING ON THIS	SKILL: First Attempt Second Attempt	PASS	FAIL
Evaluator #1:			
(Please Print) Evaluator #2:			
(Please Print)			
<i>Notice to Evaluators:</i> Candidate must signature the candidate is notified that	t he/she has failed thi	s skill and	will be

signature the candidate is notified that he/she has failed this skill and will be required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of **this skill** plus **one additional skill** from this same area of the standard.

- Skill 53: Separate, remove, and relocate charred material from uncharred material while protecting the area of fire origin for determination of fire cause. NFPA 1001 2019, 4.3.14
- **CONDITION:** Wearing full protective clothing, appropriate tools and equipment, flashlight, hoseline or water extinguisher, 2-firefighter team.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

		<u>1st. Att.</u>	<u>2nd Att.</u>
		YN	YN
1. Separate charred from uncharred mat	erial.		
2. Extinguish any smoldering material.			
3. Remove charred material to safe area	 Remove charred material to safe area. 		
4. Preserve any evidence found by leavi	ng where found.		
PERFORMANCE RATING ON THIS SM		PASS	FAIL
	First Attempt		\Box
	Second Attempt		
Evaluator Comments:			
Evaluator #1:			
(Please Print)			
Evaluator #2:			
(Please Print)			
Notice to Evaluators: Candidate must s signature the candidate is notified that h	•		

signature the candidate is notified that he/she has failed this skill and will be required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of **this skill** plus **one additional skill** from this same area of the standard.

Skill 54: Demonstrate stopping the flow of water from a discharging sprinkler head, using a wedge or stopper. NFPA 1001 2019, 4.3.14

CONDITION: Wearing full protective clothing, wedges or stopper.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

		<u>1st. Att</u>	<u>. 2nd Att.</u>
		ΥN	ΥN
1. Select appropriate tool.			
2. Stop sprinkler flow.			
PERFORMANCE RATING ON T	HIS SKILL:	PASS	FAIL
	First Attempt		
	Second Attempt		
Evaluator Comments:			
Evaluator #1:			
(Please Print)			
Evaluator #2:			
(Please Print)			
Notice to Evaluators: Candidate	•		•

signature the candidate is notified that he/she has failed this skill and will be required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of **this skill** plus **one additional skill** from this same area of the standard.

Skill 55: Operate a main control valve on the automatic sprinkler system from "open" to "closed" and then back to "open". NFPA 1001 2019, 4.3.14

CONDITION: Wearing full protective clothing.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

			<u>1st. Att</u>	<u>. 2nd Att.</u>
			ΥN	ΥN
1. Identify main control	valve.			
2. Close valve fully.				
3. Open valve fully.				
PERFORMANCE RAT	ING ON THIS S	SKILL:	PASS	FAIL
		First Attempt		
		Second Attempt		
Evaluator Comments	·			
Evaluator #1:				
(Ple	ase Print)			
Evaluator #2:				
(Ple	ase Print)			
<i>Notice to Evaluators:</i> signature the candidate		•		•

signature the candidate is notified that he/she has failed this skill and will be required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of **this skill** plus **one additional skill** from this same area of the standard.

Skill 56: Demonstrate the procedure of inspection, cleaning, and maintaining salvage covers. NFPA 1001 2019, 4.3.14

CONDITION: Salvage cover, soap, water, brushes, or broom.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

		<u>1st. Att.</u>	<u>2nd Att.</u>
		YN	YN
1. Demonstrate washing and drying salv	/age cover.		
2. Inspect cover for tears or holes.	-		
3. Mark holes if found and describe repa	air procedures.		
PERFORMANCE RATING ON THIS SH	KILL:	PASS	FAIL
	First Attempt		
	Second Attempt		
Evaluator Comments:			
Evaluator #1:			
(Please Print)			
Evaluator #2:			
(Please Print)			
Notice to Evaluators: Candidate must	• •		•

signature the candidate is notified that he/she has failed this skill and will be required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of **this skill** plus **one additional skill** from this same area of the standard.

Skill 57A:Demonstrate hydrant-to-pumper hose connections for a:Forward hose lay.NFPA 1001 2019, 4.3.15

CONDITION: Wearing full protective clothing, 2 1/2" or larger supply hose, gate valves, spanner wrench, hydrant wrench.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

	<u>1st. Att.</u>	2nd Att.
	Y N	YN
 Select correct equipment to connect to hydrant. 		
2. Loop hose around hydrant, place foot on hose, stand on		
correct side of hydrant for safety.		
3. Signal apparatus to proceed.		
4. Connect hydrant gate valves.		
5. Open hydrant completely, flush, open slowly		
6. Charge hoseline, slowly, when signal is given.		
7. Shut hydrant down slowly to prevent water hammer, che		
drain.		
PERFORMANCE RATING ON THIS SKILL:	PASS	FAIL
First Attempt		
Second Attempt		
Evaluator Comments:		
Evaluator #1:		
(Please Print)		
Evaluator #2:		
(Please Print)		
Notice to Evaluators: Candidate must sign for 2nd attem	-	•

signature the candidate is notified that he/she has failed this skill and will be required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of **this skill** plus **one additional skill** from this same area of the standard.

Skill 57B:Demonstrate hydrant-to-pumper hose connections for a:
Reverse hose lay. NFPA 1001 2019, 4.3.15

CONDITION: Wearing full protective clothing, 2 1/2" or larger supply hose, gate valves, spanner wrench, hydrant wrench, Wye gate, reducers, 1 1/2" or larger attack line with nozzle, 2-firefighter team or 3-firefigher team with 3" hose.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

		<u>1st. Att.</u> Y N	<u>2nd Att.</u> Y N
 Select equipment needed to place one service, and drop at scene, (attack hose Remove and ground 50 ft. of supply hose Kneel on hose and signal apparatus to Connect attack hose to supply hose, at 	150 ft. in length). ose from apparatus. o proceed.		
when ready.			
5. Charge hoseline and open nozzle.			
PERFORMANCE RATING ON THIS SK		PASS	FAIL
	First Attempt	Ц	
	Second Attempt		
Evaluator Comments:			
Evaluator #1:			
(Please Print)			
Evaluator #2:			
(Please Print)			
<i>Notice to Evaluators:</i> Candidate must s signature the candidate is notified that he	•		

signature the candidate is notified that he/she has failed this skill and will be required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of **this skill** plus **one additional skill** from this same area of the standard.

- Skill 58: Demonstrate a hand lay of 300 ft. of supply line, 2 1/2" or larger from a pumper to a water source. NFPA 1001 2019, 4.3.15
- **CONDITION:** Wearing full protective clothing, appropriate equipment to connect to hydrant, 300 ft. of 2 1/2" supply hose, 3-firefighter team.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

		<u>1st. Att.</u>	<u>2nd Att.</u>
		YN	YN
 Shoulder load 50ft. of hose from hos drag 50 ft per firefighter. Maintain equal distance between fire Lay entire length with no kinks or tan Connect to hydrant. 	fighters.		
PERFORMANCE RATING ON THIS S	KILL: First Attempt Second Attempt	PASS	FAIL
Evaluator Comments:			
Evaluator #1:			
(Please Print)			
Evaluator #2:			
(Please Print)			
Notice to Evaluators: Candidate must signature the candidate is notified that I required to take a 2rd and final attempt	he/she has failed thi	s skill and	will be

signature the candidate is notified that he/she has failed this skill and will be required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of **this skill** plus **one additional skill** from this same area of the standard.

Skill 59: Demonstrate the assembly and connection of the equipment necessary for drafting from a: static water supply source. NFPA 1001 2019, 4.3.15

CONDITION: Wearing full protective clothing, 2 sections 2 1/2" or larger hard suction hose, appropriate adapters and tools, roof ladder, 2-firefighter team.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

		<u>1st. Att.</u>	<u>2nd Att.</u>
		YN	YN
1. Fasten rope to strainer; aid in handling hard	suction hose		
2. Couple strainer to hard suction hose.			
3. Couple the two sections of hard suction hos	e together,		
taking care not to get dirt in coupling.			
4. Connect completed hose to apparatus.			
5. Use ladder to place hard hose on to keep ou	ut of dirt/mud.		
6. Use rubber mallet to ensure an airtight conn	ection.		
PERFORMANCE RATING ON THIS SKILL:		PASS	<u>FAIL</u>
First /	Attempt		
Seco	nd Attempt		
Evaluator Comments:			
Evaluator #1:			
(Please Print)			
Evaluator #2:	<u> </u>		
(Please Print)			
Notice to Evaluators: Candidate must sign for signature the candidate is notified that he/she	•		•

signature the candidate is notified that he/she has failed this skill and will be required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of **this skill** plus **one additional skill** from this same area of the standard.

Skill 60: Demonstrate the assembly and connection of the equipment necessary for drafting from a: Portable water tank. NFPA 1001 2019, 4.3.15

CONDITION: Wearing full protective clothing, 2 sections 2 1/2" or larger hard suction hose, appropriate adapters and tools, portable water tank, 2-firefighter team.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

		<u>1st. Att.</u>	2nd Att.
		YN	YN
1. Set-up portable water tank.			
2. Fasten rope to strainer aid in handling	hard suction hose.		
3. Couple strainer to hard suction hose.			
4. Couple the two sections of hard suction	on hose together,		
taking care not to get dirt in coupling.			
5. Connect completed hose to apparatus			
6. Use rubber mallet to ensure an airtigh	t connection.		
	····		
PERFORMANCE RATING ON THIS SK		PASS	<u>FAIL</u>
	First Attempt		
	Second Attempt		
Evaluator Comments:			
Evaluator #1:			
(Please Print)			
Evaluator #2:			
(Please Print)			
Notice to Evaluators: Candidate must signature the candidate is notified that h	• •		•

signature the candidate is notified that he/she has failed this skill and will be required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of **this skill** plus **one additional skill** from this same area of the standard.

PORTABLE EXTINGUISHERS

- Skill 61:Demonstrate the use of a portable fire extinguisher on Class
A, Class B, and Class C fire. NFPA 1001 2019, 4.3.16
- **CONDITION:** Wearing full protective clothing including eye protection, Class A-B-C portable extinguisher.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

		<u>1st. Att</u>	<u>. 2nd Att.</u>
 Select correct extinguisher for type Check pressure gauge. Pull pin and squeeze handle to tes Approach fire upwind/upgrade. Correctly extinguish simulated fire nozzle back and forth at the base of 	st extinguisher. by sweeping the	Y N	Y N
PERFORMANCE RATING ON THIS	S SKILL: First Attempt Second Attempt	PASS	FAIL
Evaluator Comments:			
Evaluator #1:			
(Please Print) Evaluator #2:			
(Please Print)			
Notice to Evaluators: Candidate me signature the candidate is notified the	at he/she has failed thi	s skill and	will be

signature the candidate is notified that he/she has failed this skill and will be required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of **this skill** plus **one additional skill** from this same area of the standard.

Skill 62:Demonstrate safety procedures when using fire service
lighting equipment. NFPA 1001 2019, 4.3.17

CONDITION: Wearing full protective clothing, power supply (mounted or portable), lights, cords, connectors, ground-fault interrupters (GFI).

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

		<u>1st. Att. 2nd Att.</u>	
		ΥN	YN
1. Start power supply.			
2. Reset ground-fault interrupter (GFI)) if necessary.		
3. Extend cord and light.			
4. Illuminate light.			
PERFORMANCE RATING ON THIS	SKILL:	PASS	FAIL
	First Attempt		
	Second Attempt		
Evaluator Comments:			
Evaluator #1:			
(Please Print)			
Evaluator #2:			
(Please Print)			
<i>Notice to Evaluators:</i> Candidate must sign for 2nd attempt failures . By this signature the candidate is notified that he/she has failed this skill and will be			

signature the candidate is notified that he/she has failed this skill and will be required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of **this skill** plus **one additional skill** from this same area of the standard.

Skill 63A:	Demonstrate safety procedures for shutting off utility
	services to a building by: Shutting off propane tank OR
	natural gas valve. NFPA 1001 2019, 4.3.18

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

			<u>1st. Att</u>	<u>. 2nd Att.</u>
			ΥN	ΥN
1. Select correct tool				
2. Turn valve(s) to th	e off position.			
PERFORMANCE R	ATING ON THIS	SKILL:	PASS	FAIL
		First Attempt Second Attempt		
Evaluator Commen	ts:			
Evaluator #1:				
	(Please Print)			
Evaluator #2:				
	(Please Print)			
		ust sign for 2nd attem at he/she has failed thi		•

signature the candidate is notified that he/she has failed this skill and will be required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of **this skill** plus **one additional skill** from this same area of the standard.

CONDITION: Wearing full protective clothing, appropriate tool for natural gas or propane tank.

Skill 63B:Demonstrate safety procedures for shutting off utility
services to a building by: Shutting off Power to structure,
main power breaker. NFPA 1001 2019, 4.3.18

CONDITION: Wearing full protective clothing.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

		<u>1st. Att</u>	<u>. 2nd Att.</u>
		ΥN	YN
1. Select correct breaker.			
2. Switch breaker to the off position.			
PERFORMANCE RATING ON THIS S	SKILL:	PASS	FAIL
	First Attempt		
	Second Attempt		
Evaluator Comments:			
Evaluator #1:			
(Please Print)			
Evaluator #2:			
(Please Print)			
Notice to Evaluators: Candidate mus			
signature the candidate is notified that			
required to take a 3rd and final attemp			
date. The 3rd attempt will consist of th	is skill plus one add	litional sk	III from this

Candidate's Signature:

same area of the standard.

- Skill 64: Operate an air monitoring instrument. NFPA 1001 2019, 4.3.21
- CONDITION: Given an air monitor and an assignment or task, the candidate shall demonstrate the ability to operate the device and recognize alarms and take actions to mitigate the hazard.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

1st. Att. 2nd Att. YN YN 1. Demonstrate the ability to operate the device according to AHJ policies and procedures. 2. Ensure all responders are wearing appropriate PPE. 3. Perform initial inspection to ensure that the monitor is serviceable. 4. Perform a bump test to ensure that the meter is functioning properly. 5. Perform a "fresh air" calibration prior to entry. 6. Monitor the area per AHJ SOPs. 7. If the monitor alarms, identify the cause for the alarm and follow AHJ SOPs. 8. Report the results according to AHJ protocol. 9. When monitoring is complete, turn off the monitor, decontaminate the monitor and return to service per manufacturer's instructions. 10. Complete required reports/supporting documentation. PERFORMANCE RATING ON THIS SKILL: PASS FAIL First Attempt Second Attempt Evaluator Comments:

Evaluator #1:______
(Please Print)

Evaluator #2:

(Please Print)

Notice to Evaluators: Candidate must sign for **2nd attempt failures**. By this signature the candidate is notified that he/she has failed this skill and will be required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of this skill plus one additional skill from this same area of the standard.

Candidate's Signature: _____

Nevada Fire Service Certification System Fire Fighter I Skills Manual

Evolution #1. As a member of a team, conduct an Offensive Attack on a **Passenger Vehicle fire.**

CONDITION: Given a 2-firefighter team, P.P.E., SCBA, attack line (150'1-3/4" with nozzle), forcible entry tools, and apparatus.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

	<u>1st. Att.</u>	<u>2nd Att.</u>
 Don structural firefighter protective clothing. Implement protective action and notification process. Completely unload attack line from apparatus. Identify automobile type of fuel. Assess and control any fuel leaks. Chock wheels of vehicle. Open attack line and flush. Set nozzle pattern between 30-60 degrees. Attack fire from uphill/upwind if possible. Attack fire, staying away from vehicle tires & bumpers. Gain entry into compartment on fire. Extinguish any ground fire, then move to fire inside vehicle. Adjust nozzle to extinguish hot spots. Overhaul all automobile compartments to find any hidden fire 	Y N	
PERFORMANCE RATING ON THIS SKILL: First Attempt Second Attempt	PASS	<u>FAIL</u>
Evaluator Comments:		
Evaluator #1:		
(Please Print)		
Evaluator #2:		
(Please Print)		
<i>Notice to Evaluators:</i> Candidate must sign for 2nd attempt failures . By this signature the candidate is notified that he/she has failed this skill and will be required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of this skill plus one additional skill from this same area of the standard.		

Evolution #2.As a member of a team, conduct an Offensive Attack on a Class
A fire, exterior fire in a Dumpster.

CONDITION: Given a 2-firefighter team, P.P.E., SCBA, attack line (150'1-3/4" with nozzle), forcible entry tools, and apparatus.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

 Don structural firefighter protective clothing. Don SCBA. Completely unload attack line from apparatus. Open attack line and flush. Set nozzle pattern between 30-60 degrees Attack fire from uphill/upwind if possible Extinguish any ground fires, then move to fire inside Dun When fire is knocked down, adjust nozzle to extinguish hot spots. Protect point of origin or cause of fire. 	1st. Att. 2nd Att. Y N Y N Image: Straight of the straight of	
PERFORMANCE RATING ON THIS SKILL:	PASS FAIL	
First Attempt Second Attemp		
Evaluator Comments:		
Evaluator #1:		
(Please Print)		
Evaluator #2:		
(Please Print)		
Notice to Evaluators: Candidate must sign for 2nd attemp	t failures . By this signat	ture

Notice to Evaluators: Candidate must sign for **2nd attempt failures**. By this signature the candidate is notified that he/she has failed this skill and will be required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of **this skill** plus **one additional skill** from this same area of the standard.

Evolution #3.	As a member of a team, conduct an Offensive Attack on an
	Interior Class A fire with tank water as supply source.

CONDITION: Given a 2-firefighter team, P.P.E., SCBA, attack line (150'1-3/4" with nozzle), forcible entry tools, and apparatus.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

		<u>1st. Att.</u> Y N	<u>2nd Att.</u> Y N
 Don structural firefighter protective clot Don SCBA. Completely unload attack line from app Select forcible entry tool and carry to d Conduct size-up of fire, determine loca Open attack line and flush line. Set nozzle pattern between 30-60 degr Force entry on door. Advance into structure searching for fir Find seat of fire and extinguish. Maintain team integrity during attack. Overhaul to find any hidden fires. 	aratus. oor. tion of fire room. ees.		
DEDEODMANCE DATING ON THE OK	1.	PASS	FAIL
PERFORMANCE RATING ON THIS SKIL	First Attempt Second Attempt		
Evaluator Comments:	First Attempt		
	First Attempt		
	First Attempt		
Evaluator Comments:	First Attempt		
Evaluator Comments: Evaluator #1:	First Attempt		

Notice to Evaluators: Candidate must sign for **2nd attempt failures**. By this signature the candidate is notified that he/she has failed this skill and will be required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of **this skill** plus **one additional skill** from this same area of the standard.

Evolution #4.As a member of a team, conduct an Offensive Attack on an
Exterior Class A fire, Ground cover fire.

CONDITION: Given a 2-firefighter team, fire protective clothing, attack line, 1" forest service line or 1" booster line or 1 ½" or 1 ¾" attack line with nozzle, apparatus

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

1st. Att. 2nd Att. ΥN ΥN 1. Don structural firefighter protective clothing. 2. Unload attack line from apparatus. 3. Attack fire from blackened side of fire. 4. Attack fire from downhill and upwind if possible. 5. Observe weather conditions for changes. 6. Maintain team integrity during attack. 7. Operate within an incident command structure. **PERFORMANCE RATING ON THIS SKILL:** PASS FAIL First Attempt Second Attempt Evaluator Comments:

Evaluator #1:_____

(Please Print)

Evaluator #2:_____

(Please Print)

Notice to Evaluators: Candidate must sign for **2nd attempt failures**. By this signature the candidate is notified that he/she has failed this skill and will be required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of **this skill** plus **one additional skill** from this same area of the standard.

Evolution #5 Demonstrate **Vertical Ventilation** in support of fire attack operation on a simulated interior structure fire.

CONDITION: Given a 4-firefighter team, P.P.E., SCBA, attack line 1 ½" or 1 ¾" attack line with nozzle (charged), pike pole, axe or chain saw, 2-24 ft. extension ladders, roof ladder, and rope.

APPLICANT PERFORMED THE FOLLOWING COMPETENCIES:

1st. Att. 2nd Att. YN ΥN 1. Don structural firefighter protective clothing. 2. Don SCBA. 3. Determine location for ventilation hole. 4. Completely unload attack line from apparatus. 5. Select forcible entry tools and carry to access point. 6. Start chain saw on ground, if being used. 7. Remove extension ladder from apparatus, carry to access point. 8. Set up extension ladder and raise to roof. 9. Properly climb ladder. 10. Properly place roof ladder on roof. 11. Determine roof integrity by sounding roof. 12. Hoist or carry tools, equipment, and houseline to roof. 13. Position second ladder as emergency escape route, away from fire. 14. Select correct location above fire to cut hole while working from roof ladder. 15. Cut ventilation hole. 16. Maintain team integrity during ventilation work. 17. Exit roof area once ventilation hole has been cut. PERFORMANCE RATING ON THIS SKILL: PASS FAIL First Attempt Second Attempt Evaluator Comments:

Evaluator #1:_____

(Please Print)

Evaluator #2:

(Please Print)

Notice to Evaluators: Candidate must sign for **2nd attempt failures**. By this signature the candidate is notified that he/she has failed this skill and will be required to take a 3rd and final attempt, no sooner than 30 days from today's date. The 3rd attempt will consist of **this skill** plus **one additional skill** from this same area of the standard.

Verification of Successful Completion Of Phase I – FFI Practical Skills Testing

To be completed by an Evaluator present for the Phase I Practical Skills Testing:

Candidate	: Date:
Locations:	
	PA 1001-2013, 5.3.7: Fire Control-passenger car fire FM Evolution # 1
— NSI	PA 1001-2013, 5.3.8: Fire Control-exterior combustibles FM Evolution #2 Piles/stacks of class A combustible materials
	Storage Containers (exterior dumpster/trash bin)
	PA 1001-2013, 5.3.10: Fire Control-interior structure fire FM Evolution #3
	PA 1001-2013, 5.3.19: Fire Control-ground cover fire FM Evolution # 4
	PA 1001-2013, 5.3.12: Vertical Ventilation FM Evolution # 5
I verify that practical sl	at I was present and personally evaluated this candidate in the following kills:
Evaluator:	

Signature: _____ Date _____